	_		4				3	+		2					1			
ı		HE INFORMATION						CELESTRA		RE SIZE	BOLT	A	В	C	D	G	Н	] '
		ISLOSED EXCEPT			NEI NOBOC	- COLD ON		CAT.NO	CODE	FLEX 150 Navy 2/0	SIZE	±0.06	MIN	±0.04	±0.015	±0.02	±0.01	
Γ		NOTE:			IS ARE IN	INCHES UNLESS	S OTHERWISE	LB301243-260	3/0 AWG	Weld 325/24 = 131 kcmil 133/.0316 259/.0227 427/.0177	1/2	4.65	2.83	0.91	0.13	1.75	0.56	D
_		SPECIFIED.  2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
			OTH			" HAS NOT PEEP IN THE SUFFIX O	Color coded barrel markings  BOLT SIZE											
		MATERIAL:	HIGI	H CONDUCT	FIVITY WR	OUGHT COPPER	₹											
(		FINISH:  ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С				
-	INSTALLATION GUIDE DIE CODE = 50  —Wire inspection hole																	
Ε	3	DIE COLOR :	C LIST		Rol 2002/9	HS 5/EC			H Be	eveled wire entr	B		)					В
_	+																	_
Α							HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.											
	4							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
		00 04-May-25	Ruby Feng	Sinia Qiu		Celestra Standa	rds Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION WROUGHT COPPER LB301243-260 NTS									
1	R	EV DATE	DWN	СНК		DESCRI	PTION	ECN	FINISH		0. NO	86-cp299	2 UN	VIT	CH	<b>(</b> E		
	_		4				3	$\uparrow$		2					1			