					I										
		4		3	$\overline{}$	2					1				
·			HE PROERTY OF CELESTRA HE REPRODUCED, USED OF		CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G +0.02	H ±0.01	•
	DISLOSED EXCEP	T FOR WHICH FURNISHED).		LB301434P-251	3/0 AWG	450/24 3/0 Weld	1/4		1.53	1.06	0.14	0.75	0.64	
									<u> </u>	!					
_															_
D	NOTE:	1 ALL DIMENSI	ONG ADE IN INCHES II	NI ESS OTHERWISE											D
	NOTE:	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S AREColor coded barrel markings													
			NDERWRITERS INC." A RES AND FLEX/24 STR	/_BOLT SIZE											
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS														
		OTHERWISE	SPECIFIED IN THE SUF												
		WITH "P".			NO.										
	MATERIAL:	HIGH CONDU	CTIVITY WROUGHT CO	OPPER											
С	FINISH:		PLATE UNLESS OTHE ATE PER MIL - T -1636		⊸G⊸										
			IO.WITH "SP" FOR SIL			A									
	Wire inspection hole														
\rightarrow	INSTALLATIO	₽ B →										\leftarrow			
	DIE CODE = 50 DIE COLOR = Orange								$\overline{}$			7			
		Ç							<u> </u>				\supset		
						\Re	eveled wire entr	v	D						
В			~			ВС	veled wire enti-	у							В
D		c(VL)us	RoHS												
		LISTED	2002/95/EC												
		WIRE CONNECTORS ZMVV/2/7/8.E513813													
															_
								CI	ELES	ΓRA	COF	RPOF	RATIO	NC	
							JYA®		6. Huar					n.	
_				_		www.h	uyaco.com	Р	anyu Di	st. G	uangz	hou 51	11495.		
Α					WIRE CONNECTORS AND SOLDERING									Α	
				LUGS FOR CODE AND FLEX CABLE											
	00 23-Aug-25	Ruby Feng Sinia Qiu	ı Celestra S	Standards Spec. Initialed.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRIC WROUGHT COPPER LB301434P-251 NTS								ID ANGLE PR	OJECTION	
	REV DATE	DWN CHK		ESCRIPTION	ECN	EINIISH			36-cp2998	3 UN	IIT		$\bigoplus $ \in	\exists	
		4	1	3	\triangle		2		-			1			
			ı							1					