								I											
			4				3	\bigvee		2					1			_	
'	THE INFO	RMATION D IN CON	ON THIS DRA	WING IS THE D NOT TO BE I	PROERTY C	OF CELESTRA, IS ED, USED OR		CELESTRA CAT.NO		RE SIZE	BOLT SIZE	A ±0.06	B MIN	C	D	G	H	'	
			FOR WHICH					CAT.NO	CODE	FLEX 200 Navy 3/0	SIZE	±0.06	IVIIIN	±0.04	±0.015	±0.02	±0.01	1	
								DB401243-250	4/0 AWG	Weld 450/24 = 182 kcmil 703/.0154	1/2	4.52	3.01	1.06	0.14	1.75	0.64		
D									l		<u> </u>	<u> </u>			l	<u> </u>	<u>I</u>	D	
	NOTI	E:		DIMENSION CIFIED.	IS ARE IN	INCHES UNLESS	SOTHERWISE												
			LIST	ED BY "UND	DERWRITE) J SERIES OF CA ERS INC." AND "C EX/24 STRANDEI	SA" FOR USE												
	1		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
			OTH			N THE SUFFIX O		BOLT SIZE											
	MATI	ERIAL:	HIGH	H CONDUCT	IVITY WR	OUGHT COPPER	?												
С	FINIS	SH:				ESS OTHERWIS	E											l c	
Ū						L - T -16366. P" FOR SILVER.						♥							
										V	G⊸∽								
									<	——A——									
	INST	ALLATIC	N GUIDE																
	INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple Wire inspection h							n hole											
	l DIE	JULUR =	: Purpie						1		В	→			\Rightarrow				
									H	7-1-1	_				TY,				
					_	/						Δ		\subseteq		\Rightarrow			
В												В							
					2002/95	SVEC			Be	eveled wire entr	У								
			LIST WIRE CONN																
			ZMVV/2/7/8																
																		l—	
	1	ı							I										
									ш	JYA®	C	ELES							
										uyaco.com		'6. Hua Раруц Г					n.		
Α																A			
A								WIRE CONNECTORS AND SO								^			
								LUGS FOR CODE AND FLEX CABLE											
	00 23-	Aug-25	-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTIC WROUGHT COPPER DB401243-250 NTS									ROJECTION	1		
	REV [DATE	DWN	СНК		DESCRI	PTION	ECN	FINISH			86-cp300)9 UI	VIIT	CH -	(E		. .	
			4				3	Δ		2			i		1			•	
					'			I					1						