			4				3	\downarrow	2	<u>)</u>				1			
I	DISCL	OSED IN COM		d not to be f	PROERTY OF C REPRODUCED,			CELESTRA CAT.NO	WIRE CODE	SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01	
-								LA1056	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	5/16	2.18	0.88	0.75	1.33	0.40	
D	D NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. Color coded marking														D		
			LIST	ED BY "UND	DERWRITERS	AND J SERIES OF CAT.NO.S ARE RITERS INC." AND "CSA" FOR USE	Bolt Size										
ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS										4	1					—	
				HERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. [H "P".					C HU A								
С		IATERIAL: INISH:	_			GHT COPPER		L L									с
C			-	-	'E PER MIL - WITH "SP" F					<u>В</u> 4							
								-	•		-						
\rightarrow	D	NSTALLATIO	42														\triangleleft
В			us	i N	IEBS	3 🖼	(R	d entry	ion Hol	e	E				В
													001				
A									HUY www.huyac		ELES 76. Hua Panyu I	ancun	Rd. Zh	iongcu	in Tow		
																	A
	00	22 440 25	Ruby Feng	Sinio Oiu		oloctro Standa	rds Spec. Initialed.								ID ANGLE PF	JECTION	
1	REV		DWN	CHK		DESCRI		ECN	FINISH ELECTRO TIN	DWG NO	1056 186-cp03	601 UI	NIT IN	CH	Ð E	\square	
	4 3						3	$\overline{\mathbb{A}}$	2					1			·