			4				3	$\downarrow$		2					1			
ı	THE IN	IFORMATION	ON THIS DRA	WING IS THE	PROERTY C	OF CELESTRA, IS		CELESTRA		RE SIZE	BOLT	A	В	С	D	G	Н	] '
			FOR WHICH I					CAT.NO	CODE	FLEX 200 Navy 3/0	SIZE	±0.06	MIN	±0.04	±0.015	±0.02	±0.01	
_								DB401243-260	4/0 AWG	Weld 450/24 = 182 kcmil 703/.0154	1/2	4.03	2.83	1.02	0.14	1.75	0.63	
D	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													D			
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	М	ATERIAL:	HIGH	H CONDUCT	ΓΙVITY WR	OUGHT COPPER	र		Color		<u>a</u>	) c						
С	FI	NISH:	SPE	CIFED PLAT	ΓE PER MI	LESS OTHERWIS L - T -16366. P" FOR SILVER.	SE .		Die		Ĭ \							С
									<b>V</b>	A	G ⊸							
$\rightarrow$	INSTALLATION GUIDE												$\leftarrow$					
r		IE CODE = IE COLOR :						-Wire inspection hole										
									H		В							
В			ر (U	)"	Pal	/			\ _				)		<del>'   '</del>			В
			LIST	FN S	2002/95	S/EC			\_В€	eveled wire entr	Ty .							
			WIRE CONN ZMVV/2/7/8.															
																		_
									Ш			ELES						
									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.									
Α								WIRE CONNECTORS AND SOLDERING									Α	
								LUGS FOR CODE AND FLEX CABLE										
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	ards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE WROUGHT COPPER DB401243-260 NTS								ROJECTION	:TION
1	REV	DATE	DWN	СНК		DESCR	IPTION	ECN	FINISH		G. NO. <b>1</b>	86-cp301	0 UN	IN	CH -	<b>(4)</b>	$\exists$	,
		_	4				3	4		2					1			
								1										