	-	4				3	\downarrow			1												
I						OF CELESTRA, IS		CELESTRA	W	RE SIZE	BOLT	А	В	С	D	G	Н	1				
			NFIDENCE AND		REPRODUC	ED, USED OR		CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04	±0.015	±0.02	±0.01					
								DB401401-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	?1/4	2.84	1.64	1.02	0.14	1.00	0.63	D				
D		IOTE:		DIMENSION CIFIED.	IS ARE IN	INCHES UNLES	S OTHERWISE															
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 																				
			OTH				P HOLE UNLESS DF THE CAT.NO.	-Color coded barrel markings BOLT SIZE														
	N	IATERIAL:	HIG	H CONDUCT		OUGHT COPPE	R															
С	C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.									g G							С					
									<	——————————————————————————————————————		->										
\rightarrow		NSTALLATIO	54					-Wire inspection hole										\leftarrow				
В									H Beveled wire entry													
			WIRE CONN ZMVV/2/7/8																			
	1																					
A								HUYA® CELESTRA CORPORA 76. Huancun Rd. Zhongcun Panyu Dist. Guangzhou 5114								un Tow	/n.					
								TITLE WIRE CONNECTORS AND SOLDERING Image: Constant of the second s														
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Stand	ards Spec. Initialed.		WR	OUGHT COPPER		401-260		CALE N		ID ANGLE PROJECTION						
I	REV	DATE	DWN	СНК	<u> </u>	DESCR	RIPTION	ECN		CTRO TIN PLATE	^{G. NO.} 1	86-cp30	12	nit IN	СН	ŧ]				
	_		4				3	4		2					1							