		1	1	3	47		2			ı		1			
	THE INFORMATION	ON THIS DRAWING IS THE	PROERTY OF CELESTRA,		CELESTRA	W	IRE SIZE	BOLT	А	l B	С	D	G	Н	
	DISCLOSED IN COI	NFIDENCE AND NOT TO BE T FOR WHICH FURNISHED.			CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04	±0.015	±0.02	±0.01	
					DB401458-251	4/0 AWG	550/24 4/0 Weld	1/4	2.57	1.70	1.19	0.16	0.63	0.73	
D															D
	NOTE:	<ol> <li>ALL DIMENSIO SPECIFIED.</li> </ol>	NS ARE IN INCHES UN												
			_B,WP,AL,AS AND J SE		∕─Color coded barrel markings										
		LISTED BY "UN ON CODE WIRI	/—BOLT SIZE												
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS														
		OTHERWISE S WITH "P".	PECIFIED IN THE SUFF	FIX OF THE CAT.NO.											
	MATERIAL:	HIGH CONDUC	TIVITY WROUGHT CO	PPER											
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE													С	
Ü			TE PER MIL - T -16366 D.WITH "SP" FOR SILV		A										
							/-Wire ins	pectio	n hole						
$\rightarrow$	INSTALLATIO		B B									$\leftarrow$			
	DIE CODE = DIE COLOR					H			_ V			Ψ\	_		
						<b>\</b>		İ	1				5)		
						\В€	eveled wire entr	у		)					
В															В
	С	(UL)US ROHS	Š.												
	1	LISTED	•												
	ZM	NV/2/7/8 E513813													
	1														
								С	FI FS	TRA	COR	POR	ΑΤΙ	)N	
							JYA®	7	6. Hua	ncun	Rd. Zh	ongcur	n Towr		
						www.h	nuyaco.com	P	anyu D	oist. G	Suangzh	10u 51	1495.		
Α					WIRE CONNECTORS AND SOLDER							.DER	ING		Α
					LUGS FOR CODE AND FLEX CA					ABLE	-				
	00 14-Dec-25	Ruby Feng Sinia Qiu	Celestra St	tandards Spec. Initialed.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THR WROUGHT COPPER DB401458-251 NTS								ANGLE PRO	DJECTION	
ı	REV DATE	DWN CHK	DES	SCRIPTION	ECN	<u> </u>	CTRO TIN PLATE	9. NO. <b>1</b>	86-cp30 <sup>-</sup>	16	init Inc	CH ] (	₩ <u> </u>	ightharpoons	i
		4		3	$\triangle$		2					1			
					ı										