			4				3	\downarrow			2					1				
1				WING IS THE D NOT TO BE F		CELESTRA, IS D. USED OR		CELESTR CAT.NO	-			BOLT SIZE	A	B	C	D	G	H		
	DISLOSED EXCEPT FOR WHICH FURNISHED.								, 261	CODE 4/0 AWG	FLEX 550/24 4/0 Weld	_	±0.06 4.18	MIN 2.83	±0.04	±0.015 0.15	±0.02	±0.01 0.71		
																			1	
D																			D	
D	N	OTE:		DIMENSION CIFIED.	IS ARE IN II	NCHES UNLES	SS OTHERWISE	SE												
							CAT.NO.S ARE		Color coded barrel markings											
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.							-BOLT SIZE											
			OTH			HAS NOT PEE I THE SUFFIX														
	м	H CONDUCT																		
С	SPECIFED PLATE PER MIL - T -16366.									A	⊶G⊸∽							с		
	SUFFIX CAT.NO.WITH "SP" FOR SILVER.													-						
										—Wire inspection hole										
\rightarrow	> INSTALLATION GUIDE																		4	
		IE CODE = IE COLOR =																		
	Beveled wire entry																			
В																	В			
				TED	2002/95/8															
	WIRE CONNECTORS ZM/VV/2/78.E513813																			
									HUYA® CELESTRA CO 76. Huancun Rd. Zł											
			www.huyaco.com Panyu Dist. Guangzhou 51149																	
А							TITLE WIRE CONNECTORS AND SOLDERING													
										LUGS FOR CODE AND FLEX CABLE										
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Stand	dards Spec. Initialed			WR	OUGHT COPPER	-	243-261		CALE N	rs ^{thr}				
	REV	DATE	DWN	СНК		DESC	RIPTION	EC	CN		CTRO TIN PLATE	/G. NO.	86-cp30	27	INIT IN	CH -	Ψt		ا I	
			4				3	4			2					1				