									1															
		4 3					3	\mathbf{A}	2					1										
1		E INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS					CELESTRA	WIRE SIZE BOLT A			вС		D	G	Н	1								
	DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODU DISLOSED EXCEPT FOR WHICH FURNISHED.					JCED, USED OR			CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04	±0.015	5 ±0.02	±0.01]					
									LB403843	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	3/8	4.35	2.63	1.03	0.14	1.75	0.63						
D											•	•							D					
	N	IOTE:		DIMENSION CIFIED.	NS ARE IN	INCHES U	JNLESS O	THERWISE																
	 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. Color coded barrel markings 																							
			OTH	-FIX CAT.N ERWISE SF H "P".																				
	N	IATERIAL:	HIGH	H CONDUC	TIVITY WR	OUGHT C	OPPER																	
С															С									
				A																				
\rightarrow	D	NSTALLATIO	54						_─Wire inspection hole ←															
В		DIE COLOR :		DUS	Rol 2002/95	HS stec				н н э	eveled wire entr	В <u> </u>							в					
			ZMVV/2/7/8																					
												С	CELESTRA			CORPORAT		ION	1					
										THUYA 76. Huancun Rd. Zhongcun Town.														
										www.huyaco.com Panyu Dist. Guangzhou 511495.														
A										WIRE CONNECTORS AND SOLDERING														
										LUGS FOR CODE AND FLEX CABLE														
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra	Standards	Spec. Initialed.		MATERIAL HIG	H-CONDUCTIVITY PRT OUGHT COPPER	. NO. LB4	03843	S	CALE N	TS	RID ANGLE PROJECTION							
	REV	DATE	DWN	СНК		DE	ESCRIPT	TION	ECN	FINISH		0. N/O	86-cp30	34 U	NIT	СН	ŧ							
			4					3	\triangle		2					1			-4					
					•				I					•										