	,					I											
		4			3	\forall		2					1				
'		ON ON THIS DRAWING				CELESTRA		IRE SIZE	BOLT	А	В	С	D	G	Н] '	
		PT FOR WHICH FURN		JOCED, OSED OK		CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04	±0.015	±0.02	±0.01	4	
						LB401434-250	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	1/4	3.40	1.53	1.06	0.14	0.75	0.64		
D	NOTE:	4 ALL DIM	ENICIONIC A DE	IN INCHES UNLES	e OTHEDWISE											D	
	NOTE.	SPECIFII		IN INCHES UNLES	3 OTHERWISE												
		2. ALL DA,[B,LA,LB,WP	AND J SERIES OF C	AT.NO.S ARE												
		LISTED E	BY "UNDERWI	RITERS INC." AND " FLEX/24 STRANDE	CSA" FOR USE												
		ON COD	E WIKES AND	FLEX/24 STRAINDE	D CABLES.	∕−Color coded barrel markings											
				H "L" HAS NOT PEEF ED IN THE SUFFIX (
		WITH "P"		ED IN THE SUFFIX (DE THE CATINO.).											
	MATERIAL	HIGH CC	NDUCTIVITY	WROUGHT COPPE	R												
С	FINISH:	ELECTO	R-TIN PLATE	SE											c		
C				R MIL - T -16366. "SP" FOR SILVER.					<u> </u>								
		SUFFIX	JAT.NO.WITH	SP FOR SILVER.					G								
							-	——A——		_>							
_																	
\rightarrow	INSTALLAT DIE CODE	ION GUIDE = 54						∕-Wire ins	pectio	n hole						\leftarrow	
	DIE COLOF	R = Purple					T 8///	/	_				_				
							й		В	<u></u>		/		\			
							1					\in		\Rightarrow			
В									ı			В					
	l ,		Police				\В€	eveled wire entr	у		,						
	'		2002/95/EC														
		WIRE CONNECTORS ZMVV/2/7/8.E513913															
	1																
									С	ELES	TRA	COF	RPOI	RATIO	NC	1	
		1			-			JYA®	7	'6. Hua	ncun F	Rd. Zh	nongci	ın Tow			
		+ +-						nuyaco.com		Panyu D	ist. G	uangz	hou 5	11495.			
Α		+				TITLE WIRE CONNECTORS AND SOLDERING											
						LUGS FOR CODE AND FLEX CA											
							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION										
		, ,				WROUGHT COPPER LB401434-250 NTS											
ı	REV DATE		CHK	DESCR	RIPTION	ECN		CTRO TIN PLATE	^{J. INU.} 1	86-cp303	88 "	IN	СН	Ψ -]	
		4			3	4		2					1				
						I											