		4				3	$\bigvee$		2					1			_
ı				ROERTY OF CELESTF EPRODUCED, USED C			CELESTRA		RE SIZE	BOLT	A	В	С	D	G	Н	] '
		EPT FOR WHICH					CAT.NO	CODE	FLEX 200 Navy 3/0	SIZE	±0.06	MIN	±0.04	±0.015	±0.02	±0.01	1
							LB403843-250	4/0 AWG	Weld 450/24 = 182 kcmil 703/.0154	3/8	4.48	2.61	1.06	0.14	1.75	0.64	
D	NOTE	4 11	DIMENSIONS	ADE IN INICHEO I	INII 500 0	THE DAME				•					•		D
	NOTE:		CIFIED.	ARE IN INCHES U	JNLESS C	THERWISE											
		LIS	TED BY "UNDE	WP AND J SERIES ERWRITERS INC." AND FLEX/24 STF	AND "CSA	A" FOR USE											
_	1						∕−Color coded barrel markings										
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															
	MATERIA	.: HIG	H CONDUCTI	VITY WROUGHT C	OPPER												
С	FINISH:		ELECTOR-TIN PLATE UNLESS OTHERWISE														lс
				: PER MIL - T -1636 VITH "SP" FOR SIL													
										G⊸∽							
								-	——A——		_>						
$\triangle$	INSTALLA	TION GUIDE															4
	DIE CODE	= 54 R = Purple							/-Wire ins	pectio	n hole						
	DIL COLC	it = i dipie						4		В	<b>→</b>		4				
								H						<b>-</b>			
_										1	<b>┴</b>				$\supset$		
В	Beveled wire entry										В						
			RoHS					De	eveled wire enti	у							
		LISTED															
		ZMVV/2/7/8.E513913															
	-																
		<u> </u>	<del></del>					I	<u> </u>	T =							-
						_		HI	JYA®	C	<b>ELES</b> '6. Hua						
			-						uyaco.com		o, Hua Panyu D					11.	
Α				TITLE WIRE CONNECTORS AND SOLDERING										A			
														KING			
								LUGS FOR CODE AND FLEX CABLE									
	00 31-Oct-2	0 31-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDUCTIVITY PRT. NO. LB403843-250 SCALE NTS THRID ANGLE PROJECTION										
ı	REV DATE	DWN	CHK	D	ESCRIP	ΓΙΟΝ	ECN	FINISH ELEC	CTRO TIN PLATE	9. NO. <b>1</b>	86-cp304	11 UI	IN TIV	CH -	<b>⊕</b> €	$\underline{}$	] ,
		4			,	3	$\triangle$		2					1			-
	•			•			I					•					