| | | | | | | | | 1 | | | | | | | | | | |
|---------------|-------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|---------------------------------|------------|----------------------------|---------------------------------------------------------------------------------------------------|----------------------------------------------|------------------------------|-----------------------------------|---------------------|------------|----------|-----------|--------------|------------|-------|-----|
| | | | 4 | | | | 3 | \bigvee | | 2 | | | | | 1 | | | _ |
| ' | | | | AWING IS THE F D NOT TO BE F | | F CELESTRA, IS | | CELESTRA | | RE SIZE | BOLT | Α | В | C | D | G | H | ' |
| | | | | FURNISHED. | | | | CAT.NO | CODE | FLEX 200 Navy 3/0 | SIZE | ±0.06 | MIN | ±0.04 | ±0.015 | ±0.02 | ±0.01 | - |
| | | | | | | | | LB405601P-250 | 4/0 AWG | Weld 450/24 = 182 kcmil 703/.0154 | 5/16 | 3.66 | 1.79 | 1.06 | 0.14 | 1.00 | 0.64 | |
| D | | _ | | | | | | | | | • | | | • | | | | D |
| | NOT | E: | | CIFIED. | S ARE IN I | NCHES UNLES | SS OTHERWISE | | | | | | | | | | | |
| | | 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. | | | | | | | | | | | | | | | | |
| _ | 1 | Color coded barrel markings | | | | | | | | | | | | | | | | |
| | PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". | | | | | | | | | 1 | BOLT SIZE | | | | | | | |
| | MAT | MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER | | | | | | | | | | | | | | | | |
| С | FINIS | SH: | | | _ | ESS OTHERWI | SE | | | | | | | | | | | |
| | | | | CIFED PLAT FIX CAT.NO. | | T -16366. ' FOR SILVER. | | | | | | | _ | | | | | С |
| | | | | | | | | | | — | G⊸∽ | | | | | | | |
| | | | | | | | | | V | ——A—— | | — ⊳ | | | | | | |
| \rightarrow | | ALLATION | | | | | | | | | | | | | | | | 4 |
| | | CODE = 54 COLOR = 1 | | | | | | | | -Wire ins | pectio | n hole | | | 1 | | | 7 |
| | | | · | | | | | | H | | В | — ⊳ | | , | | \ | | |
| | | | | | | | | 1 | 1 | | | | <u> </u> | _ | Ψ + + + + | | | |
| В | | | | | | | | | | | | | | | | | | |
| | | Beveled wire entry | | | | | | | | | В | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | WIRE C | ONNECTORS 2/7/8.E513913 | | | | | | | | | | | | | | | |
| |] | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | JYA® | C | ELES | | | | | | |
| | | | | | | | | | | | | 6. Hua | | | | | | |
| Α | | | | | | | | www.huyaco.com Panyu Dist. Guangzhou 511495. | | | | | | | | | A | |
| ^ | | | | | | | | WIRE CONNECTORS AND SOLDER | | | | | | | | | ^ | |
| | | | | | | | | | LUGS FOR CODE AND FLEX CABLE | | | | | | | | | |
| | 00 16 | 16-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. | | | | | MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION WROUGHT COPPER LB405601P-250 NTS | | | | | | | | | | | |
| 1 | REV [| DATE | DWN | CHK | | DESC | RIPTION | ECN | FINISH ELEC | CTRO TIN PLATE | ^{G. NO.} 1 | 86-cp304 | 46 U | nit In | СН | ⊕ £ | |] , |
| | | | 4 | | | | 3 | 4 | | 2 | | | | | 1 | | | |
| | • | | | | - | | | I | | | | | | | | | | |