			4				3	+		2					1			
ı	THE IN	NFORMATION	ON THIS DRA	WING IS THE	PROERTY C	OF CELESTRA, IS		CELESTRA		IRE SIZE	BOLT	A	В	С	D	G	Н] '
			FOR WHICH					CAT.NO	CODE	FLEX 200 Navy 3/0	SIZE	±0.06	MIN	±0.04	±0.015	±0.02	±0.01	-
_								LB401243P-250	4/0 AWG	Weld 450/24 = 182 kcmil 703/.0154	1/2	4.88	3.01	1.06	0.14	1.75	0.64	
D	N	OTE:		DIMENSION CIFIED.	IS ARE IN	INCHES UNLES	S OTHERWISE											D
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																	
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	M	IATERIAL:	HIGH	H CONDUCT	ΓΙVITY WR	OUGHT COPPE	R		Color		<u>B</u>) - c						
С	F	INISH:	SPE	CIFED PLAT	ΓE PER MI	LESS OTHERWIS L - T -16366. P" FOR SILVER.	SE											
									∇	——A——	G⊸							
\rightarrow	INSTALLATION GUIDE													\leftarrow				
<i>V</i>		IE CODE = IE COLOR :							-Wire inspection hole									
									H		В							
В			ω. U),,,	Į	/										=)		В
			1191	FD US	2002/95	TS 5/Ec			\B€	eveled wire enti	ry							
			WIRE CONN ZMVV/2/7/8															
										IV A®		ELES						1
									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.								n.	
Α						_		TITLE WIRE CONNECTORS AND SOLDERING									-	
								LUGS FOR CODE AND FLEX CABLE										
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Standa	ards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PR LB401243P-250 NTS								ROJECTION	
1	REV	DATE	DWN	CHK		DESCR	IPTION	ECN	FINISH		0.110	86-cp305	0 UNI			(E		
			4				3	4		2					1			
								1										