	i							I										
			4				3	\bigvee		2					1			_
'				AWING IS THE I D NOT TO BE F		OF CELESTRA, IS		CELESTRA		IRE SIZE	BOLT	A	В	С	D	G	Н	'
			FOR WHICH					CAT.NO	CODE	FLEX 200 Navy 3/0	SIZE	±0.06	MIN	±0.04	±0.015	±0.02	±0.01	1
								LB401243P-260	4/0 AWG	Weld 450/24 = 182 kcmil 703/.0154	?1/2	4.77	2.83	1.02	0.14	1.75	0.63	
D		XTE	4 411	DIMENSION	0.455.11		00.071.150.4405											D
	NC.	DTE:		CIFIED.	S ARE IN	INCHES UNLES	SS OTHERWISE											
		 ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 																
_	ł							Color coded barrel markings										
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".									BOLT SIZE								
	MA	ATERIAL:	HIG	H CONDUCT	IVITY WR	OUGHT COPPE	ER E											
С	FIN	NISH:				ESS OTHERWI	SE											
				CIFED PLAT FIX CAT.NO.		L - 1 -16366. P" FOR SILVER.						V	_					
											G⊸∽							
									<	——A——		—⇒						
\rightarrow		STALLATIO																4
		E CODE = 5 E COLOR =								-Wire ins	pectio	n hole			1			7
			·						H		В	→		,		\		
									1			_ 	<u>!</u>	_	Υ - -			
В									\			1 1			' '			В
		Beveled wire entry																
			LOUS	ROHS 2002/95/EC														
		WIRE	ISTED E CONNECTORS V/2/7/8.E513813															
											С	ELES	TRA	CO	RPOI	RATIO	ON	
										JYA®		'6. Hua						
								www.huyaco.com Panyu Dist. Guangzhou 511495.									1,	
Α							TITLE WIRE CONNECTORS AND SOLDER							RING		A		
		LUGS FOR CODE A							AND	ND FLEX CABLE								
	00 1	0 16-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER LB401243P-260 NTS									
1	REV	DATE	DWN	СНК		DESCF	RIPTION	ECN	FINISH ELEC	CTRO TIN PLATE	G. NO. 1	86-cp30	55 U	nit In	CH -	() -[\exists	
		,	4	. '			3	\triangle	•	2			Ì		1			
	•				'			I					'					