		4		0	<u></u>								
	THE INFORMATION	4 I ON THIS DRAWING IS TH	 	3 A. IS	CELESTRA	2 WIRE SIZE BOLT		BOLT	<u> </u>	С	D G	н	
	DISCLOSED IN CO	NFIDENCE AND NOT TO B T FOR WHICH FURNISHED	E REPRODUCED, USED O	R	CAT.NO	CODE	FLEX	SIZE ±	.0.06 MII	V ±0.04 ±0	0.015 ±0.02	±0.01	
					LB403801P-261	4/0 AWG	550/24 4/0 Weld	3/8 3	3.77 1.8	3 1.14 0).15 1.00	0.71	
D													D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.												
		2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S AREColor coded barrel markings											
			NDERWRITERS INC." A RES AND FLEX/24 STR		/_BOLT SIZE								
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS												
				FFIX OF THE CAT.NO.									
	MATERIAL			ODDED									
_	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE											С	
С	I INIOI I.	SPECIFED PL											
	SUFFIX CAT.NO.WITH "SP" FOR SILVER.												
							/-Wire ins	spection h	nole				
	INSTALLATION GUIDE											•	4
	DIE CODE = 54 DIE COLOR = Purple										 		\
		•											
						Be	veled wire entry	ν	D				
В	·										В		
	CUL) US ROHS,												
		2002/95/E											
	W Zi	RE CONNECTORS AVV/2/7/8.E513813											
	-												—
								CFI	LESTR	A CORE	PORATIO)N	
							JYA®	76.	Huancu	ın Rd. Zhor	ngcun Towr		
						www.h	uyaco.com	Par	nyu Dist.	Guangzho	ou 511495.		
Α				TITLE W	ERING		Α						
				LUGS FOR CODE AND FLEX CABLE									
	00 16-Dec-25	Ruby Feng Sinia Qiu	Feng Sinia Qiu Celestra Standards Spec. Initialed.			MATERIAL HIGH WRO	H-CONDUCTIVITY OUGHT COPPER LB403801P-261 SCALE NTS THRID ANGLI					OJECTION	
1	REV DATE	DWN CHK	DE	SCRIPTION	ECN	FINISH ELEC	TRO TIN PLATE	G. NO. 186	-cp3063	UNIT INCH	7 1		1
		4	I	3	Φ	- 2	2		Ī		1		
					1								