																			$\overline{}$
			4				3		\bigvee		2					1			_
•				AWING IS THE D NOT TO BE F		OF CELESTRA, IS ED, USED OR	5		CELESTRA CAT.NO		RE SIZE	BOLT	A ±0.06	B MIN	C ±0.04	D	G ±0.02	H ±0.01	'
			FOR WHICH							CODE	FLEX 550/24 = 222								
									LB253801P-260	250 kcmil	kcmil 4/0 Weld	?3/8	3.80	1.83	1.10	0.14	1.00	0.68	
_																			_
D	NO ⁻	TE:	1 ΔΙΙ	DIMENSION	IS ADE IN	INCHES UNLE	SS OTHER	WISE											D
	100	16.		CIFIED.	O AILL IIV	INCHES ONLE	LOG OTTILIX	WISE											
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE								Color coded barrel markings									
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.							/_BOLT SIZE										
	1	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
		TERIAL:				OUGHT COPF						G							
С	FIN	IISH:				LESS OTHERV L - T -16366.	VISE				———A———								С
			SUF	FIX CAT.NO	.WITH "SF	" FOR SILVER	₹.												
		—Wire inspection hole																	
\rightarrow			ON GUIDE						1	Ť	7-7-	В	>		/		\		\leftarrow
	DIE CODE = 62 DIE COLOR = Yellow							\in		\Rightarrow									
		lacksquare																	
										\Ве	eveled wire entr	У							
В					V														В
			C	L)U S	Rol- 2002/98	IS S/EC													
			LIS	TED															
			WIRE CONI ZMVV/2/7/8																
	1																		
		-	I																
										ш	JYA®	C	ELES						
											nuyaco.com		76. Hua Panyu E						
А																			Α
, ,		THE THE							WIRE CONNECTORS AND SOLDERING								, ,		
								LUGS FOR CODE AND FLEX CABLE											
	00 04	04-May-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				. Initialed.	MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER LB253801P-260 SCALE THRID ANGLE PROJECT								ROJECTION				
1	REV	DATE	DWN	СНК		DESC	CRIPTION		ECN	FINISH ELEC	CTRO TIN PLATE	G. NO. 1	86-cp310	00 0	nit In	ICH	⊕ €	\Box	
			4				3		4		2					1			
	•				-				I					-					