			4				3	$\downarrow$	2	2				1				
I	DISCL	OSED IN COM		D NOT TO BE F	PROERTY OF CELE REPRODUCED, USE			CELESTRA CAT.NO	WIRE CODE	SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01		
-						]		LA1014P-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	1/4	2.27	0.64	0.75	1.66	0.39		
D	N	OTE:		DIMENSION CIFIED.	S ARE IN INCHE	SUNLESS	OTHERWISE	Color coded marking									D	
			LIST	ED BY "UND	3,WP AND J SEF ERWRITERS IN	C." AND "CS	Bolt Size											
				ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS														
			OTH	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".														
0		IATERIAL: INISH:			IVITY WROUGH LATE UNLESS C													
С			SPE	CIFED PLAT	E PER MIL - T -1 WITH "SP" FOR	6366.				<u>В</u>							С	
								-	- /	Α	-							
$\rightarrow$	D	ISTALLATIO	42														$\triangleleft$	
B	D		us	k N	IEBS <sup>(3</sup>	Rohs	CE		R	d entry	ion Ho	<u>e</u>	E				В	
A													001					
								- HUYA® www.huyaco.com CELESTRA CORPOL 76. Huancun Rd. Zhongcu Panyu Dist. Guangzhou 5						in Tow	Town.			
									TITLE WIRE CONNECTORS AND SOLDERING								A	
		00.4							LUGS FOR CODE AND FLEX CABLE									
	00 Rev	DATE	Ruby Feng	Sinia Qiu CHK		DESCRIP	Is Spec. Initialed.	ECN	FINISH ELECTRO TIN	OPPER LA10	14P-260 186-cp03	_	NT NIT	CH	O E	$\square$		
	4 3						$\triangle$	2					1			· 		