			_		1				+				ı					
			4				3	3	\vee	2		_	<u> </u>		1			,
				RAWING IS THE ND NOT TO BE		OF CELESTRA, I	IS		CELESTRA	WIRE		BOLT	Α	В	C	R	ID . O O4	
				H FURNISHED.					CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04		±0.01	ł
									LA1056P-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0254	5/16	2.33	0.70	0.75	1.66	0.39	
D											133/.0234							D
	N	OTE:		L DIMENSION ECIFIED.	NS ARE IN	I INCHES UNL	LESS OTHE	RWISE	Color coded marking									
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 																
						ERS INC." AN _EX/24 STRAN			Bolt Size									
			0			_" HAS NOT PI IN THE SUFF				DIE COLOR	® Y		د					
	М	IATERIAL:	HI	GH CONDUCT	TIVITY WI	ROUGHT COP	PPER		L		1 2 1							
С	FI	INISH:	SF	ECIFED PLAT	TE PER M	ILESS OTHER IIL - T -16366. P" FOR SILVE					B	-	<u> </u>					С
									-	·	1	-						
\rightarrow		ISTALLATION																\leftarrow
		IE COLOR =								В	Inspect	on Hol	_					
]-	. R	- Inspect	OH HOI	_					
									∓ [7		
В						^	./		₽, †		· 			/	/			В
		ւ(ՄԼ)		Ž a N	IFR	5 3	RoHS		<u> </u>									
		LICTE	, .	• 1	ILD					Beveled	d entry							
		WIRE CONN	ECTOR							Bevele	a Gridly							
	1																	
												FIFS	STRA	COI	RPO	RΔTI	ON	1
	H									HUY	CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.							
	$\vdash \vdash \vdash$											Panyu Dist. Guangzhou 511495.						
Α									TITLE WIRE CONNECTORS AND SOLDERING							SING		Α
								FOR CODE AND FLEX CABLE										
	00	01-Jul-25	Ruby Fer	g Sinia Qiu		Celestra Sta	andards Spe	ec. Initialed.		MATERIAL HIGH-CONDUC WROUGHT CO		56P-260		CALE N		RID ANGLE PI	ROJECTION	1
ı	REV	DATE	DWN	СНК		DES	CRIPTION	V	ECN	FINISH ELECTRO TIN F	5,446,446	186-cp03	313 U	nit IN	CH -	(E		l .
			4				3		Δ	2	<u> </u>		i		1			•
					1								ı					