| | | 4 | | 3 | $\overline{}$ | 2 | | | | | | 1 | | |
|---|--|---|--|---------------------------------------|---|------------|-----------------|--------------|--------------|------------|---------|------------------|--------------|---|
| · | | | HE PROERTY OF CELESTR BE REPRODUCED, USED O | | CELESTRA CAT.NO | CODE | RE SIZE FLEX | BOLT SIZE | A ±0.06 N | B MIN ± | | O G 015 ±0.02 | H ±0.01 | |
| | DISLOSED EXCEPT | FOR WHICH FURNISHE | D. | | DB355643-260 | 350 kcmil | 350 Navy | ?5/16 | | | | 18 1.75 | 0.79 | l |
| | | | | | | | , | -!! | Į. | | Į. | | | ĺ |
| _ | | | | | | | | | | | | | | |
| D | NOTE: | 1 ALL DIMENS | IONS ARE IN INCHES U | INI ESS OTHERWISE | | | | | | | | | | D |
| | SPECIFIED. | | | | | | | | | | | | | |
| | | | A,LB,WP AND J SERIES | Color coded barrel markings BOLT SIZE | | | | | | | | | i | |
| | | | JNDERWRITERS INC." / RES AND FLEX/24 STR | | | | | | | | | | | |
| | PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS | | | | | | | | | | | | | |
| | | OTHERWISE WITH "P". | SPECIFIED IN THE SU | FFIX OF THE CAT.NO. | | | | | | | | | | |
| | MATERIAL: | | ICTIVITY MIDOLICI IT C | | | | | | | i | | | | |
| | | | | | | | | | | | | | С | |
| С | FINISH: | SPECIFED P | LATE PER MIL - T -1636 | | | | | | | | | | | |
| | | SUFFIX CAT. | NO.WITH "SP" FOR SIL | VER. | | | ^ | | | | | | | |
| | | | | | | | ∕-Wire ins | enaction | holo | | | | | |
| _ | | | | | | | Specifor | i iioie | | 1 | | | | |
| | INSTALLATION DIE CODE = | | | H B | | | | | | | | | \leftarrow | |
| | DIE COLOR : | = Red | | | | † \ | | | | | | | | |
| | | | | | | | | | h D | | ı | | | |
| | Beveled wire entry | | | | | | | | | | | | | |
| В | | _(Մ I) ոջ | PoHS | | | | | | | | | | | В |
| | | | 2002/95/EC | | | | | | | | | | | |
| | | LISTED WIRE CONNECTORS ZMVV/2/7/8 E513913 | | | | | | | | | | | | |
| | | ENTY VISIT IN LATER TO | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | CI | FLEST | RΔ(| CORP | ORATI | ON | |
| | | | | | | H | JYA® | 70 | 6. Huand | cun Ro | l. Zhon | gcun Tov | /n. | |
| | | | | _ | | www.h | uyaco.com | P | anyu Dis | st. Gua | ngzhou | u 511495 | | |
| Α | | | | | WIRE CONNECTORS AND SOLDERING | | | | | | | Α | | |
| | | | | | LUGS FOR CODE AND FLEX CABLE | | | | | | | | | |
| | 00 23-Aug-25 | Ruby Feng Sinia Q | iu Celestra | | MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THI WROUGHT COPPER DB355643-260 NTS | | | | | | | | | |
| | REV DATE | DWN CH | | ESCRIPTION | ECN | EINIISH | | 10. 110 | 36-cp3144 | UNIT | INCH | 1 1 | \exists | |
| | | 4 | <u> </u> | 3 | \triangle | | 2 | | | İ | | 1 | | 1 |
| | | | ' | | | | | | | • | | | | |