

THE INFORMATION ON THIS DRAWING IS THE PROPERTY OF CELESTRA, IS DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISCLOSED EXCEPT FOR WHICH FURNISHED.

CELESTRA CAT.NO	WIRE SIZE		BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01
	CODE	FLEX							
DB413801-262	400 kcmil	400 Navy	7/32	3.62	1.83	1.38	0.19	1.00	0.86

D
NOTE:




1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.
2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.

PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".

MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER

FINISH: ELECTRO-TIN PLATE UNLESS OTHERWISE SPECIFIED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.

INSTALLATION GUIDE
DIE CODE = 76
DIE COLOR = Blue



00	17-Jan-26	Ruby Feng	Sinia Qiu	Celestra Standards Spec. Initiated.
REV	DATE	DWN	CHK	DESCRIPTION

		TITLE		CELESTRA CORPORATION	
		WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE		76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.	
MATERIAL	HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO.	DB413801-262	SCALE	NTS
FINISH	ELECTRO TIN PLATE	DWG. NO.	186-cp3186	UNIT	INCH

