		_	1	_	4	_			1					
	THE INFORMATION (	4 ON THIS DRAWING IS THE P	ROERTY OF CELESTRA I	3	T CELESTRA	CELESTRA WIRE SIZE		BOLT	1	В	1		ın	,
	DISCLOSED IN CONF	FIDENCE AND NOT TO BE REFOR WHICH FURNISHED.			CAT.NO	CODE	FLEX	SIZE	A ±0.06	MIN	C ±0.04	R	ID ±0.01	
	DIOCOGED EXOCIT	TON WHIGHT ON HOLES.			WP1414-094	14-10 AWG	-	1/4	1.18	0.65	0.41	0.53	0.13	
D	NOTE:	ALL DIMENSIONS     SPECIFIED.	ARE IN INCHES UNL	Color coded marking  Bolt Size									D	
_		2. ALL DA,DB,LA,LB LISTED BY "UNDI ON CODE WIRES  PRE-FIX CAT.NO. OTHERWISE SPE WITH "P".	HUYA®									_		
	MATERIAL:	HIGH CONDUCTI			В									
С	FINISH:	ELECTOR-TIN PL SPECIFED PLATE	ATE UNLESS OTHER EPER MIL - T -16366. VITH "SP" FOR SILVE	A A									С	
В	INSTALLATIO DIE CODE = - DIE COLOR =		BS3	(€		R	Inspection	on Hol	e	E				В
	1													_
A						HUY www.huyaco	D.com F	ELES '6. Hua Panyu [	incun Dist. G	Rd. Zh uangz	ongcu hou 5'	in Tow 11495.	n.	A
, ,				WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00 01-Dec-25	Ruby Feng Sinia Qiu	Feng Sinia Qiu Celestra Standards Spec. Initialed.			MATERIAL HIGH-CONDUC WROUGHT CO	CTIVITY PRT. NO.	14-094		CALE N7	THR	ID ANGLE PI	ROJECTION	
	REV DATE	DWN CHK		CRIPTION	ECN	FINISH ELECTRO TIN F	81118 118	86-cp00	32	VIIT	CH 4	<b>+</b> E	$\Box$	
		4		3	4	2		•			1	•		1