		4 3		\bigvee	2			1						
'			THE PROERTY OF CELESTRA BE REPRODUCED, USED OF		CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06 N		.04 ±0.0	G 15 ±0.02	H ±0.01	
	DISLOSED EXCEP	T FOR WHICH FURNISH	ED.		DB513801	500 kcmil	500 Navy	3/8		.93 1.		_	0.99	
							,	<u> </u>	<u> </u>	Į.	<u> </u>			
_														_
D	NOTE:	1. ALL DIMENS	IONS ARE IN INCHES U	NI FSS OTHERWISE										D
			A,LB,WP AND J SERIES UNDERWRITERS INC." A	Color coded barrel markings										
		ON CODE W	/_BOLT SIZE											
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS													
		OTHERWISE WITH "P".	SPECIFIED IN THE SUF	FFIX OF THE CAT.NO.										
	MATERIAL:		UCTIVITY WROUGHT CO											
_	FINISH:		IN PLATE UNLESS OTHE											
С	FINISH.	SPECIFED F	LATE PER MIL - T -1636		C C									
		SUFFIX CAT	.NO.WITH "SP" FOR SIL'	/ER.			Α							
	/-Wire inspection hole													
_	INIOTALLATI	ON OUR			T 8////	/ · · · · · · · · · · · · · · · · ·	opodion	11010						
	INSTALLATI DIE CODE =	87		H H B									\leftarrow	
	DIE COLOR	= Brown				1						\equiv		
							I	I	ή D		'			
_						\Be	veled wire entr	ry	_					_
В		շ(Մլ)սջ	RoHS											В
		LICTED	2002/95/EC											
		WIRE CONNECTORS ZMVV/2/7/8.E513913												
								CE	ELEST	RAC	ORPO	DRATIO	ON	
							JYA®	76	3. Huand	cun Rd.	Zhong	cun Tow	'n.	
				_		www.h	uyaco.com	Pá	anyu Dis	st. Guar	ngzhou	511495.		_
А					WIRE CONNECTORS AND SOLDERING								Α	
					LUGS FOR CODE AND FLEX CABLE									
	00 01-Jul-25	Ruby Feng Sinia C	iu Celestra S		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCA							ROJECTION		
ı	REV DATE	DWN CHI	< DE	SCRIPTION	ECN	EINIICH		10. N.O.	36-cp3213	UNIT	NTS INCH	(1)	\rightarrow	
		4	<u> </u>	3	<u> </u>		2			İ		1		
			•		I					•				