			4		I		3	\downarrow		2					1			
I			I ON THIS DRA			F CELESTRA, IS D. USED OR		CELESTRA CAT.NO			BOLT	A	B	C	D	G	H]
			FOR WHICH					DB511243	CODE 500 kcmil	FLEX 500 Navy	SIZE 1/2	±0.06 5.00	MIN 3	±0.04	±0.015 0.22	±0.02	±0.01 0.99	1
																		1
D																		D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																	
						J SERIES OF C RS INC." AND "	AT.NO.S ARE CSA" FOR USE	Color coded barrel markings										
		ON CODE WIRES AND FLEX/24 STRANDED CABLES.							-BOLT SIZE									
			OTH				P HOLE UNLESS DF THE CAT.NO.											
	N	IATERIAL:	HIGI	H CONDUCT		DUGHT COPPE												
С	F	INISH:	SPE	CIFED PLAT	E PER MIL			G										
	SUFFIX CAT.NO.WITH "SP" FOR SILVER.																	
								-Wire inspection hole										
\rightarrow	INSTALLATION GUIDE DIE CODE = 87															\triangleleft		
		IE COLOR :	-															
												E))		I			
D	Beveled wire entry															В		
				ED														
			ZM///2/7/8	E513913														
A									HUY			ELESTR		RA CORPORATI		RATIO	ON	
								www.h		. Huancun Rd. Zhongcun Town. nyu Dist. Guangzhou 511495.								
						_										A		
									WIRE CONNECTORS AND SOLDERING									
	00	23-Aug-25	Ruby Feng	Sinia Oiu		Celestra Stand	ards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO SCALE							ND ANGLE PF	ROJECTION	-
	REV	DATE	DWN	CHK			RIPTION	ECN	FINISH	OUGHT COPPER	NG NO	11243 86-cp32	 14 U	NIIT	CH -	ÐE	\square	
	L	1	4	I			3	4		2					1			1
L								I					•					