			4				3	\downarrow			2					1					
1			I ON THIS DRA			F CELESTRA, IS		CELEST CAT.N			RE SIZE	BOLT	A	В	C	D	G	Н]		
			FOR WHICH					LB5114	-	CODE 500 kcmil	FLEX 500 Navy	SIZE 1/4	±0.06 4.89	MIN 1.94	±0.04	±0.015 0.22	±0.02	±0.01 0.99	-		
									-					-	-	-			1		
-																					
D	N	OTE:	1. ALL	DIMENSION	IS ARE IN	INCHES UNLE		D													
		 SPECIFIED. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 								Color coded barrel markings											
		ON CODE WIRES AND FLEX/24 STRANDED CABLES.							-BOLT SIZE												
						HAS NOT PER															
				IERWISE SP H "P".	ECIFIED I	N THE SUFFIX															
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																				
С	FI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE								~G> (
C						L - T -16366. " FOR SILVER		A													
			001																		
											<i>∖</i> –Wire	inspectio	n hole								
\rightarrow	IN	ISTALLATIO	ON GUIDE																		
		IE CODE = IE COLOR =																			
										-				Γ	E		\exists				
										Be	eveled wire e	entry	[Ċ							
																			в		
			c	JUS	Roh	IS ÆG															
			LIST	TED																	
			WIRE CONF ZMVV/2/7/8	ECTORS E513913																	
		1	1																		
A									HUYA												
										www.huyaco.com							n.				
																			A		
								Image: Wire connectors and soldering Image: Wire connectors and soldering LUGS FOR CODE AND FLEX CABLE													
																		OJECTION			
			Ruby Feng				dards Spec. Initialed.									1					
	REV	DATE	<u>4</u>	СНК	I	DESC	RIPTION 3		CN	ELEC	TRO TIN PLATE		186-cp32	30 °	IN	ICH 1	Ψ -]		
			4				3	4			۷					I					