					I									$\overline{}$
		4	3		$\overline{}$	2			,		1		_	
'			HE PROERTY OF CELESTR BE REPRODUCED, USED O		CELESTRA CAT.NO		RE SIZE	BOLT SIZE	A ±0.06	B MIN	C ±0.04 ±	D G		i '
		FOR WHICH FURNISHE			LB511243P-260	CODE 500 kcmil	FLEX 500 Navy	?1/2				0.23 1.7		ł
							,		I	I	I		<u> </u>	
_														
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE												D	
	11012.	SPECIFIED.												
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE Color coded barrel markings												
		_BOLT SIZE												
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS													l —
		OTHERWISE WITH "P".	SPECIFIED IN THE SU	FFIX OF THE CAT.NO.	AT.NO.									
	MATERIAL.		ICTIVITY MIDOLICUIT C	ODDED		Die		Ĭ						
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE											C		
С	FINISH:	SPECIFED P	LATE PER MIL - T -1636											
		SUFFIX CAT	NO.WITH "SP" FOR SIL	VER.		1 2	Α							
							∕-Wire ins	snection	n hole					
_	INSTALLATION GUIDE													
	DIE CODE =	87			H									
	DIE COLOR :	= Brown												
						\			† D					
	Beveled wire entry													l _
В		ւ(ՈՐ)ոշ	RoHS											В
		LIOTED	2002/95/EC											
		WIRE CONNECTORS ZMVV/2/7/8.E513813												
	1													
								CI	ELEST	RA (CORI	PORAT	ΙΟΝ	
							JYA®	7	6. Huan	cun R	d. Zho	ngcun To	own.	
				_		www.huyaco.com Panyu Dist. Guangzh					angzh	ou 51149	95.	A
Α					WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00 23-Aug-25	Ruby Feng Sinia C	iu Celestra		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID WROUGHT COPPER LB511243P-260 NTS									
1	REV DATE	DWN CH	DE	ESCRIPTION	ECN	EINISH			36-cp3243	UNI		$\dashv \bigoplus$		
	,	4		3	Δ		2					1		'
			•		I					•				