	_		4				3	+		2					1			
ı		NFORMATION LOSED IN CON				F CELESTRA, IS D, USED OR		CELESTRA CAT.NO		RE SIZE	BOLT SIZE	A ±0.06	B MIN	C	D ±0.015	G .0.02	H ±0.01	, I
		OSED EXCEPT						DB511243-251	CODE -	FLEX 535.3 kcmil 1325/24 (500 MCM NOM)	1/2		3.55	1.89	0.26	1.75	1.17	
	NOTE:  1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.  2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER  C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.													D 				
	SUFFIX CAT.NO.WITH "SP" FOR SILVER.  INSTALLATION GUIDE DIE CODE = 87 DIE COLOR = Brown  Wire inspection hole												$\leftarrow$					
B		Beveled wire entry  LISTED WIRE CONNECTORS ZANVOZTR ESTABIA														B —		
		I								A -		ELFO	TDA	005	ם מכו	) ATI	יאכ	
А							HUYA® 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.										•	
								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
		04-Nov-25	<u> </u>	<b></b>			rds Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE NTS THRID ANGLE PROJECTION NTS TH						OJECTION			
1	REV	DATE	DWN	CHK	ı	DESCRI		ECN		TRO TIN PLATE	G. NO. 1	86-cp325	0   0	IN(		Ψ τ		
	-		4				3	4	:	2					1			