														$\overline{}$
		4		3	∇	2						1		_
·			THE PROERTY OF CELESTR D BE REPRODUCED, USED O		CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04 ±	D 0.015 ±0.		
	DISLOSED EXCEPT	FOR WHICH FURNISH	HED.		WP751243-191	750 kcmil	- -	1/2		2.78		0.27 1.7		1
						!	1		<u> </u>	!	Į	'		1
_														_
D	NOTE:	1 ALL DIMEN	SIONS ADE IN INCHES I	INII ESS OTHEDWISE										D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													
			LA,LB,WP AND J SERIES			∕─Color coded barrel markings								
			"UNDERWRITERS INC." VIRES AND FLEX/24 STR	/_BOLT SIZE										
_			AT.NO.WITH "L" HAS NOT											
		OTHERWIS	E SPECIFIED IN THE SU											
		WITH "P".												
	MATERIAL:	HIGH CONI	<u> </u>											
С	FINISH:		TIN PLATE UNLESS OTH PLATE PER MIL - T -1636		A ————————————————————————————————————									
			T.NO.WITH "SP" FOR SIL											
	—Wire inspection hole													
\rightarrow	INSTALLATIO	. B → B												
DIE CODE = 106 DIE COLOR = Black							7:							
						\Re	eveled wire entr	rv.	D					
В			√			De	veled wire end	ıy						B
Ь		c(VL)us	RoHS,											
		LISTED	2002/95/EC											
		WIRE CONNECTORS ZMVV/2/7/8.E513913												
								CI	ELEST	TRA	COR	PORA	TION	1
							JYA®	70	6. Huan	cun R	d. Zho	ngcun T	own.	
						www.huyaco.com Panyu Dist. Guangzhou 5					ou 51149	95.		
Α					WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00 23-Aug-25	Ruby Feng Sinia	Oiu Calastra		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE								1	
	REV DATE	DWN CH		Standards Spec. Initialed. ESCRIPTION	ECN	EINIISH	DUGHT COPPER DW		243-191 36-cp3306	UN	NTS IT INCH	$\dashv \bowtie$		
	3,112	4		3			2	10	opood		IIIUCI	1		1
		•	I	Č	+	•	_			I		•		