		4		+	0	ı	4	
	THE INFORMATION	ON THIS DRAWING IS THE	PROERTY OF CELESTRA, IS	CELESTRA	2 WIRE SIZE	BOLT A	B C D G	
	DISCLOSED IN CON	FIDENCE AND NOT TO BE I FOR WHICH FURNISHED.		CAT.NO	CODE FLE	X SIZE ±0.06	MIN ±0.04 ±0.015 ±0.02 =	±0.01
				WP751243-191	750 kcmil –	1/2 5.39	2.78   1.90   0.27   1.75	1.17
D								D
	NOTE:	<ol> <li>ALL DIMENSION SPECIFIED.</li> </ol>	IS ARE IN INCHES UNLESS OTHERW	/ISE				
	2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE						S	
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.				/ BOLT SIZE			
_			D.WITH "L" HAS NOT PEEP HOLE UN					
		OTHERWISE SP	ECIFIED IN THE SUFFIX OF THE CA		No olo	exp. C		
		WITH "P".			Die	73 7		
	MATERIAL:		TIVITY WROUGHT COPPER					
С	FINISH:	SPECIFED PLAT	LATE UNLESS OTHERWISE 'E PER MIL - T -16366.		^	⊸-G-⊸		С
		SUFFIX CAT.NO	.WITH "SP" FOR SILVER.		A -	<u> </u>		
					~\ <b>\</b>	ire inspection hole		
_	INICTALLATIC	NI CLUDE						
	INSTALLATIC DIE CODE = 1	106			H	B		
	DIE COLOR =	: Black				<u> </u>		
					\	, j	·	
_					─Beveled wir	e entry		
В								В
	C.	SLJUS RoHS						
	WIRE ZMV	STED CONNECTORS V/2/7/8.E513813						
					HUY	R CELES	TRA CORPORATIO	
					- www.huyaco.c		icun Rd. Zhongcun Town st. Guangzhou 511495.	
Α						-		-
					WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE			
							SCALE THRID ANGLE PRO.	IFOTION .
	00 14-Dec-25		Celestra Standards Spec. I		MATERIAL HIGH-CONDUCTIV WROUGHT COPPL FINISH	R WP751243-191	NTS A	T.
1	REV DATE	DWN CHK	DESCRIPTION	ECN	ELECTRO TIN PLAT	TE DWG. NO. 186-cp3306	S INCH   W L	7
		4	1 3	//\	2		1 4	