						上											
		4			3	2					1	1			,		
	DISCLOSED IN CO	N ON THIS DRAWING NFIDENCE AND NOT	TO BE REPRO			CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01		
	DISLOSED EXCEP	T FOR WHICH FURN	ISHED.			LB751243-241		1600/24 = 646	1/2	6.10	3.00	1.94	0.27	1.75	1.20		
						LB/31243-241		kcmil	1/2	0.10	3.00	1.54	0.27	1.73	1.20		
Ь																_	
D	NOTE:	1. ALL DIME	NSIONS ARE	IN INCHES UNLE	SS OTHERWISE											D	
		SPECIFIE															
				AND J SERIES OF RITERS INC." AND			∕─Color coded barrel markings										
				FLEX/24 STRAND	/-Color coded barrel markings												
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS															
		OTHERW WITH "P".		D IN THE SUFFIX	OF THE CAT.NO.												
	MATERIAL:			WROLIGHT COPP	FR												
_														_			
С	FINISH.	⊸-G⇒									С						
		SUFFIX C	AI.NO.WITH	"SP" FOR SILVER				——A——		—⇔							
_	INIOTALLATI	INSTALLATION GUIDE						Wire inspection hole									
	DIE CODE =		B B														
	DIE COLOR	= Black				ı	1				1		<u> </u>				
							<b>*****</b>				Ī		+++	_)			
							Be	eveled wire entr	v		)						
В			<b>✓</b>						,							В	
	С		RoHS 2002/95/EC														
	W.	LISTED  IRE CONNECTORS  MVV/2/7/8.E513813															
		MVV/2//8.E513913															
	1																
									С	ELES	TRA	COI	RPOI	RATIO	NC		
										HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.							
					www.huyaco.com Panyu Dist. Guangzhou 511495.									Α			
Α		TITLE WIRE CONNECTORS AND S								SOL	SOLDERING						
		LUGS FOR CODE AND FLEX CA							ABL	E							
	00 02-Nov-25	Ruby Feng Sini	a Qiu	Celestra Stan	dards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PR UROUGHT COPPER LB751243-241 NTS							ROJECTION			
	REV DATE		HK		RIPTION	ECN	FINISH			86-cp33	18	NIIT	CH -	<b>(</b> E	$\exists$		
		4	-	1	3	$\triangle$		2		•			1	<u> </u>			
				1							'						