THE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISLOSED EXCEPT FOR WHICH FURNISHED. DISLOSED EXCEPT FOR WHICH FURNISHED. 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISES OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".		H ±0.01 1.40
DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISLOSED EXCEPT FOR WHICH FURNISHED. CAT.NO CODE FLEX SIZE ±0.06 MIN ±0.04	±0.015 ±0.02 :	±0.01 1.40
DISLOSED EXCEPT FOR WHICH FURNISHED. LB113801 1000 kcmil 1000 Navy 3/8 6.35 2.80 2.27 LB113801 1000 kcmil 1000 Navy 3/8 6.35 2.80 2.27 LB113801 1000 kcmil 1000 Navy 3/8 6.35 2.80 2.27 LB113801 1000 kcmil 1000 Navy 3/8 6.35 2.80 2.27 Color coded barrel markings LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".		
NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".		D
SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".		
LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".		
OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".		
MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER		
C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.		С
/-Wire inspection hole		
INSTALLATION GUIDE DIE CODE = 125 DIE COLOR = White		
Beveled wire entry Beveled wire entry		В
WIRE CONNECTORS ZMVV/D7/IB E513813		_
HUYA® CELESTRA CO 76. Huancun Rd. Zh www.huyaco.com Panyu Dist. Guangz	hongcun Town	
A WIRE CONNECTORS AND SOLUGS FOR CODE AND FLEX C	CABLE	A
	TS THRID ANGLE PRO.	DJECTION
	ICH \bigcirc	
4 3 2	1	