			4				3		7		2				1			_
'					PROERTY OF OR				CELESTRA CAT.NO	· ———	RE SIZE	BOLT SIZE	B MIN	C	D	G	H	l '
			FOR WHICH					-	LB141434FI	CODE P- #14-#10	FLEX			±0.04		±0.02	±0.01	ł
									260	AWG	_	1/4	1.39	0.41	0.05	0.75	0.17	1
																		1
D																		D
	N N	OTE:		DIMENSION CIFIED.	IS ARE IN IN	CHES UNLESS	OTHERWISE											1
			2 All	DA DRIAI	R WP AND .I.	SERIES OF CA	AT NO S ARE											1
			LIST	ED BY "UNI	DERWRITERS	S INC." AND "C	SA" FOR USE						/	BOLT	SIZF			1
			ON	CODE WIRE	S AND FLEX	/24 STRANDEI	O CABLES.			~	√		χ	T	0			l —
							HOLE UNLESS				Huya	<u>-(-X</u>		;				1
				IERWISE SF H "P".	ECIFIED IN 1	HE SUFFIX O	F THE CAT.NO.				\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			<u> </u>				1
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER G												1					
С	l FI	INISH:	ELE	CTOR-TIN F	LATE UNLES	S OTHERWIS	E				<u> </u>							
C					TE PER MIL -													С
			501	FIX CAT.NC).WITH "SP" F	OK SILVER.				\ \ \	Color co	ded barr	el ma	rkings				1
																		1
_									Wire inspection hole									
1		ISTALLATION IE CODE =							A		B B	1	~	D				\leftarrow
	D	IE COLOR =	=						<u> </u>					#				1
		Beveled wire entry										1						
										2010	nou who only							1
В				,														В
		c	(UL) _{US}	.RoHS														1
		,	ISTED	2002/95/EC														1
			RE CONNECTORS IVV/2/7/8.E513913															1
																		l_
																		1
										HUY		ELES	TRA	CO	RPO	RATIO	NC	1
												76. Hua					n.	1
										www.huyac	o.com	Panyu [JIST. G	uangz	znou 5	11495.		1.
Α										WIRE CONNECTORS AND SOLDERING A								
									 	LUGS	FOR COD	e and) FL	EX C	CABL	E		
	00	27-Oct-25	Ruby Feng	Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID AND WROUGHT COPPER LB141434FP-260 NTS							RID ANGLE PE	ROJECTION	ЛОИ
	REV	DATE	DWN	СНК		DESCRI			ECN F	INISH ELECTRO TIN	DWG NO	186-cp33		NIIT	ICH -	(E	\exists	
			4				3	1	\	2	ı	•	 	71	1	•		1
					ı			\top	_				1					