		4				3	4	7	2	2				1			
ı				PROERTY OF CELES			Ť	CELESTRA	WI	RE SIZE	BOLT	В	С	D	G	Н	
	DISCLOSED IN C			REPRODUCED, USED	OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
								DB081058F	#8 AWG	#8 Weld 37/24 = 14.9 kcmil	#10	1.18	0.42	0.08	0.62	0.22	
							L			14.9 KCIIIII							
D																	D
D	NOTE:		DIMENSION CIFIED.	IS ARE IN INCHES	UNLESS (OTHERWISE											
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. BOLT SIZE									SIZE							
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	MATERIAL	: HIGI	H CONDUCT	TIVITY WROUGHT	COPPER					G							
С	FINISH:	ELE	CTOR-TIN P	PLATE UNLESS OT	HERWISE					<u> </u>							С
C				TE PER MIL - T -16 D.WITH "SP" FOR S													
		301	FIX CAT.NO	WITH SP FOR S	OILVEK.				*	Color cod	ed barı	rel ma	rkings				
									Wire inspection hole								
	INSTALLAT	ION GUIDE						8		BB			D				\leftarrow
	DIE COLOF												‡				
									_		I		Ŷ				
									⁻Beve	eled wire entry							
В				√													В
Ь		c(V	L)us	.RoHS													
		110:		2002/95/EC													
		LIS WIRE CONF															
		ZMVV/2/7/8	I.E513813														
_	4																l —
		1						1 1		. 1							
									HUY		ELES					_	
											76. Hua					n.	
^									www.huyac	0.00111	Panyu [JIST. G	uangz	21100 5	11495.		_
Α								TI	TLE WIRE	CONNECT	ORS	AND) SOI	LDEF	RING		Α
						<u></u>		+	LUGS	FOR CODE	E ANI) FL	EX C	CABL	Ε		
	00 23-Aug-2	5 Ruby Feng	Sinia Qiu	Celestr	a Standard	s Spec. Initialed.		М.	ATERIAL HIGH-CONDU WROUGHT C	JCTIVITY PRT. NO.	31058F	S	CALE N	TS THE	RID ANGLE PF	ROJECTION	
	REV DATE		СНК	[DESCRIP	TION		ECN FII	NISH ELECTRO TIN		86-cp33	72	INIIT	ICH .	(E	\exists	
		4		I		3	Δ	\	2	I				1	-		'
	•			I			4	_				I		·			