4 3 2				$\overline{}$
	l	1		
DICCLOSED IN CONFIDENCE AND NOT TO BE DEDDODUCED. LISED OD	BOLT B C	D G	Н	ı
DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISLOSED EXCEPT FOR WHICH FURNISHED. CAT.NO CODE FLEX #8 Weld 37/24 =	SIZE MIN ±0.04 ±	±0.015 ±0.02	±0.01	
DB083801F-250 #8 AWG #8 Veid 37/24 = 14.9 kcmil	3/8 1.73 0.63	0.05 1.00	0.23	
D			D)
NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.				
2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE				
LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE	∠BOLT SIZE			
ON CODE WIRES AND FLEX/24 STRANDED CABLES.	BOLIC		_	_
PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.				
OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".				
MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER G	G			
C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE	—⊶ 			
SPECIFED PLATE PER MIL - T -16366.				,
SUFFIX CAT.NO.WITH "SP" FOR SILVER. Color codec	d barrel markings			
27	pection hole			4
INSTALLATION GUIDE DIE CODE = 21	D ☐		\triangleleft	_
DIE COLOR = Red	 			
Beveled wire entry	I Y			
Develed wife entry				
В			В	š
LICTED				
LISTED WHE CONNECTORS 2MV/927/R ES18912				
			<u> </u>	
LILLY AR CE	LESTRA COR	PORATIO	N	
	. Huancun Rd. Zho		٦.	
	nyu Dist. Guangzh	nou 511495.		
A TITLE WIRE CONNECTO	TITLE WIRE CONNECTORS AND SOLDERING A			ı.
	LUGS FOR CODE AND FLEX CABLE			
00 07 Oct 05 Dubu Fana Sinia Oiu Calastra Standarda Sana Initialed MATERIAL HIGH-CONDUCTIVITY PRT. NO.	SCALE	THRID ANGLE PRO	DJECTION	
WOODITIEST TO THE TENTON OF TH	LINIT	-	$\exists \bot$	
4 JESCRIPTION ELECTROTIN PLATE STATE 186	6-cp3377 INC	1	7	
	I	I	_	