			4		I		3	$\downarrow$		2	2		I		1						
1					PROERTY OF CELES			-	ESTRA	WI	RE SIZE	BOLT	В	С	D	G	Н	1			
			FIDENCE AND		REPRODUCED, USEI	DOR		CA	T.NO	CODE	FLEX #8 Weld 37		MIN	±0.04	±0.015	±0.02	±0.01				
								DB081	058F-251	#8 AWG	#8 Weid 37 14.9 kcm		1.17	0.41	0.08	0.63	0.23				
D		OTE:	1 411		IS ARE IN INCHES											D					
		OTE.		CIFIED.																	
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.										BOLT SIZE										
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																				
	м	IATERIAL:	HIGI		TIVITY WROUGHT		G														
С	F	INISH:			LATE UNLESS O					'							С				
-					TE PER MIL - T -16 WITH "SP" FOR \$																
									Color coded barrel markings												
										Wire inspection hole											
$\rightarrow$		INSTALLATION GUIDE DIE CODE = 21																			
		IE COLOR =																			
										Beve	led wire er	ntry		Ť							
В			<u> </u>	2	$\checkmark$											I		в			
			C	<b>J</b> us	RoHS																
			ZMVV/2/7/8																		
																		—			
А													CTD/			ידאם					
										HUY	A®		ELESTRA CORPO 76. Huancun Rd. Zhong								
										www.huyaco.com			Panyu Dist. Guangzhou 511495.								
									TITLE WIRE CONNECTORS AND SOLDERING								A				
									LUGS FOR CODE AND FLEX CABLE												
	00	23-Aug-25	3-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATE	ERIAL HIGH-CONDU WROUGHT C		NO. DB081058F-2		SCALE N	TS	RID ANGLE PF	LE PROJECTION					
	REV	DATE	DWN	СНК		DESCRIF	PTION	EC	N <sup>FINIS</sup>		DWG.			INIT	ICH -	ŒE					
			4	· /			3	$\Delta$		2	•		İ		1			•			
					-																