	-				_			1										
			4				3	\bigvee	7		2				1			
•					PROERTY OF REPRODUCED	CELESTRA, IS), USED OR			CELESTRA CAT.NO	-	RE SIZE	BOLT SIZE	B MIN	C ±0.04	D	G ±0.02	H ±0.01	'
			FOR WHICH]	-		CODE	FLEX #8 Weld 37/24 =							
									DB081401F-26 ²	#8 AWG	14.9 kcmil	?1/4	1.64	0.44	0.08	1.00	0.23	
D	l .																	D
	N	IOTE:		CIFIED.	IS ARE IN IN	ICHES UNLESS	OTHERWISE											
			2. ALL	DA.DB.LA.L	B.WP.AL.AS	AND J SERIES	OF CAT.NO.S ARE	<u> </u>										
			LIST	ED BY "UNI	DERWRITER	RS INC." AND "C	SA" FOR USE	_						BOLT	SIZE			
	4		ON	CODE WIRE	S AND FLE?	K/24 STRANDEI	CABLES.				Q		1					
						HAS NOT PEEP THE SUFFIX O	HOLE UNLESS				Huya	-(<u></u> с					
				H "P".	LCIFILD III	THE SUFFIX O	THE CATINO.							<u>.</u>				
	N	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER G																
С	F	INISH:	ELE	CTOR-TIN F	LATE UNLE	SS OTHERWIS	E				2	-7						С
C					TE PER MIL	- T -16366. FOR SILVER.												C
			301	FIX CAT.NC	.WIIII SF	FOR SILVER.				*	Color cod	ed barre	el mar	kings				
_	l									Wire inspection hole								
		NSTALLATIO DIE CODE = 1							4		B		1	D		<u> </u>		\leftarrow
	D	IE COLOR =	= Red											‡				
		Beveled wire entry																
										Deve	oled whe entry							
В				,														В
		c ((Jr) ^{US}	RoHS														
		,	ISTER	2002/95/EC														
			E CONNECTORS VV/2/7/8.E513813															
											 A ® C	ELES	TRA	CO	RPOI	RATIO	NC	
										HUI		'6. Huar					n.	
										vww.huyac	co.com F	Panyu D	ist. G	uangz	hou 5	11495.		
Α									TITL	TITLE WIRE CONNECTORS AND SOLDERING A								
									+	LUGS FOR CODE AND FLEX CABLE								
	00	14-Dec-25	Ruby Feng	Sinia Qiu		Celestra Standa	ds Spec. Initialed.		MAT	ERIAL HIGH-COND	UCTIVITY PRT. NO.	404E 004	S	CALE		RID ANGLE PI	ROJECTION	
	REV		DWN	CHK		DESCRI			ECN FINI	WROUGHT (DWG NO	401F-261 86-cp339	2 UI	NT IN	CH -	() E	\exists	
			4	OT III	l	22001(1	3	Λ		2	IPLAIE I	00-ch998	<u>- </u>	IIN	<u>сн ј</u> 1	¥	7	l
	-		4		I		5	4	Δ	۷			I		'			