								1									
			4				3	<b>T</b>		2				1			
ı					PROERTY OF C REPRODUCED, I			CELEST		WIRE SIZE	BOLT	В	С	D	G	Н	
			FOR WHICH		REPRODUCED, I	JSED OR		CAT.N	CODE		SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
							-	DB081401	F-261 #8 AW	#8 Weld 37/24 = 14.9 kcmil	?1/4	1.64	0.44	0.08	1.00	0.23	
									<b>!</b>	<u>'</u>	<u> </u>						
D																	D
	N	IOTE:		DIMENSION CIFIED.	IS ARE IN INC	HES UNLESS	OTHERWISE										
					B,WP AND J S												
					DERWRITERS S AND FLEX/2		SA" FOR USE					/	BOLT	SIZE			
_	┨											7	1				—
							HOLE UNLESS F THE CAT.NO.		—(( <del>))</del>		<u>`</u> ( <del>/</del> )	- <del> </del>	;				
				H "P".									V				
	M	MATERIAL:	HIG	H CONDUCT	FIVITY WROU	GHT COPPER				~	3						
С	F	INISH:			PLATE UNLES: FE PER MIL - T		E										С
					WITH "SP" F					0-1	-ll l						
									\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Color co	ded bari	rei ma	rkings				
								ကို/		Wire i	nspectio	n hole	7				
		NSTALLATIO	ON GUIDE					45.43.	Pie	В	поросио	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	D		$\vdash$		
	D	DIE CODE =	21							< \h		<b>-</b>	Ţ				7
	"	DIE COLOR :	= Kea					<u> </u>					+				
									\_B	eveled wire entry							
					,					·							
В			, (U	.)	V												В
			C	<b>り</b> us	ROHS 2002/95/EC	1											
			LIS	ΓED		)											
			WIRE CONI ZMVV/2/7/8														
										N/ AR	CELES	TRA	COI	RPOF	RATIO	NC	
									HU	YA® '	76. Hua					_	
		<del>                                     </del>								aco.com	Panyu [						
Α								-	TITLE WIF	E CONNEC	ORS	ANI	SOI	DFR	NIG		Α
		WIRE CONNECTORS AND SOLDERII LUGS FOR CODE AND FLEX CABLE															
											L AINI		CALE		L ID ANGLE PF	O IECTION	
			Ruby Feng		Ce		ds Spec. Initialed.			HT COPPER DB08	1401F-26	1	N <sup>-</sup>		_	OJECTION	
1	REV	DATE	DWN	CHK		DESCRI	PTION	ECN	FINISH ELECTR	DTIN PLATE DWG. NO.	186-cp33	92	INIT IN	CH   1	<b>⊕</b> €		
			4				3	$\triangle$	2				-	1	-		
	•				•			I				•					