	-								I									
		4			3			\bigvee	2					1				
ı					PROERTY OF				CELESTRA		RE SIZE	BOLT	В	С	D	G	Н	
			FOR WHICH		KEPKODOCED	, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
									LB081058F-25	50 #8 AWG	#8 Weld 37/24 = 14.9 kcmil	#10	1.17	0.41	0.08	0.63	0.23	
										'		-						
D																		D
	٨	NOTE:		DIMENSION CIFIED.	NS ARE IN IN	CHES UNLESS	S OTHERWISE											
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. BOLT SIZE																	
_	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".											_						
	N	MATERIAL:	HIGI	H CONDUC	TIVITY WROL	JGHT COPPER	₹				G	;						
С	F	FINISH:	ELE	CTOR-TIN F	PLATE UNLES	SS OTHERWIS	SE .				2	머						С
C					TE PER MIL -	T -16366. FOR SILVER.												
			301	FIX CAT.NC	D.WIIT OF I	TOR SILVER.				*	_Color cod	led bar	rel ma	rkings				
									Wire inspection hole								4	
		NSTALLATION DIE CODE =							43		BB_		-	D				\leftarrow
		DIE COLOR :												‡				
										\ D		I		Ť				
										Beve	eled wire entry							
В					V	•										I		В
D			c(V	L)US	RoHS	S,												
			1101	ren .	2002/95/EO													
	1		WIRE CONF															
	-																	—
	\vdash	1	I		<u> </u>						A .		·TF -		DD 0 :	D 4 = 1 :		
										HUY		ELES					_	
										www.huyac		76. Hua Panyu [
А																		Α
^											CONNECT							^
										LUGS	FOR COD	E ANI) FL	EX C	CABL	Е		
	00	23-Aug-25	Ruby Feng	Sinia Qiu	C	Celestra Standa	ards Spec. Initialed.		М	ATERIAL HIGH-CONDI WROUGHT (UCTIVITY PRT. NO.	058F-250) s	CALE N	TS THE	RID ANGLE PF	ROJECTION	
	REV		DWN	CHK		DESCR			ECN FI	NISH ELECTRO TIN	DWG NO	186-cp33		INIIT	ICH -	(E	\exists	
		1	4	I	l		3	/	Λ	2					1	-		
	_		•		ı		J	_	†	<u>-</u>			I		•			