_								-										
		4				3	7	2			1							
ı					PROERTY OF REPRODUCED	CELESTRA, IS			CELESTRA	· -	RE SIZE	BOLT	В	С	D	G	Н	
			FOR WHICH		REPRODUCEL	, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
							_		LB081434F-2	50 #8 AWG	#8 Weld 37/24 = 14.9 kcmil	1/4	1.37	0.48	0.07	0.75	0.23	
									,	<u>'</u>	•							
D																		D
	NO	DTE:		DIMENSION CIFIED.	IS ARE IN IN	CHES UNLESS	OTHERWISE											
		<ol> <li>ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.</li> </ol>								BOLT SIZE								
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	FIN	NISH:			PLATE UNLE	SS OTHERWIS	E											С
						FOR SILVER.				. <b></b>	∕–Color co	ded hari	rel ma	rkinas				
									/	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	/ 30101 301	aca ban	Cillia	ikiiigo				
									<u>څ</u> ړ/	Codel	Wire in	nspectio	n hole	;				
$\rightarrow$		STALLATIC							45° 43°	100	В		-⇔l	D				$\leftarrow$
		E CODE = 2 E COLOR =							Į.					1				
									Beveled wire entry									
В																		В
Ь		-1		V														Ь
		C		RoHS 2002/95/EC	1													
		WIFE	ISTED E CONNECTORS															
		ZMV	VV/2/7/8.E513913															
			<u> </u>								_	VEL EC	TD			DATI		
	$\vdash$									HUY		<b>ELES</b> 76. Hua						
										www.huyac		76. Hua Panyu [					11.	
Α	$\sqcup$																	Α
					_			WIRE CONNECTORS AND SOLDERING										
		LUGS FOR CODE AND FLEX CABLE																
	00 2	27-Oct-25	Ruby Feng	Sinia Qiu	(	Celestra Standa	rds Spec. Initialed	i.	M	ATERIAL HIGH-CONDI WROUGHT (		434F-250	) s	cale N	TS THE	RID ANGLE PF	ROJECTION	
ı	REV	DATE	DWN	CHK		DESCRI	PTION		ECN FI	NISH <b>ELECTRO TIN</b>	DWG. NO.	186-cp34	00	init In	ICH -	<b>⊕</b> £		ı
			4				3	4		2					1			
					•			I					•					