			4		I		3		7		2		1		1			
I	DISCL	OSED IN CON	FIDENCE ANI	D NOT TO BE	PROERTY OF CI				CELESTRA CAT.NO		RE SIZE FLEX	BOLT SIZE	B	C +0.04	D ±0.015	G ±0.02	H ±0.01]
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					LB081058FF 251		#8 Weld 37/24 = 14.9 kcmil	_	1.17	0.41	0.08	0.63	0.23	1
								ľ			I		1	1	1	1		
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													D				
2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.											_/_	BOLT						
			OTH		D.WITH "L" HA PECIFIED IN TH													
	м	IATERIAL:	HIGI	H CONDUC		GHT COPPER		G										
С	FI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
	Color coded barrel markings																	
\rightarrow	INSTALLATION GUIDE DIE CODE = 21 DIE COLOR = Red								Beveled wire entry									
В			.6	.	V													в
	LISTED WIRE CONNECTORS ZMVV/217/8.E513913														_			
A										HU \	R]
													76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.					
									TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								A	
		00 A. 07							N	ATERIAL HIGH-COND	UCTIVITY PRT. NO.		5	CALE	THE	E RID ANGLE PF	OJECTION	-
	00 Rev	23-Aug-25 DATE	Ruby Feng	Sinia Qiu CHK	Ce	DESCRI	rds Spec. Initialed.				DWG, NO.	058FP-2	51	N.	TS ICH	¢ و	\square	
		1	4				3	4		2			-	11	1			J
								I										