| | _ | | | | | | ı | | | | | | | | | |
|---|--|---------------|---|---|-----------------------|-------|---------------------------|---------------------------------|--|----------|--------|------------|--------|--------------|-----------|---|
| | | 4 | | | 3 | | \bigvee | 2 | | | | | 1 | | | |
| ı | | | | PROERTY OF CELESTRA REPRODUCED, USED OR | | | CELESTRA | | RE SIZE | BOLT | В | С | D | G | Н | |
| | | EPT FOR WHICH | | REPRODUCED, USED OR | | | CAT.NO | CODE | FLEX | SIZE | MIN | ±0.04 | ±0.015 | ±0.02 | ±0.01 | |
| | | | | | | | DB061034F-25 | 51 #6 AWG | #6 Weld 61/24 = 24.6 kcmil | #10 | 1.29 | 0.46 | 0.08 | 0.75 | 0.27 | |
| | | | | | | | | • | | | • | | | • | | |
| D | | | | | | | | | | | | | | | | D |
| | NOTE: | | DIMENSION CIFIED. | IS ARE IN INCHES UN | ILESS OTHERWISE | : | | | | | | | | | | |
| | 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE MUDES AND FLEX (A CTRANDER CARLES) BOLT SIZE | | | | | | | | | | | | | | | |
| _ | | ON | ON CODE WIRES AND FLEX/24 STRAINDED CABLES. | | | | | | | | | | _ | | | |
| | PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". | | | | | | | | | | | | | | | |
| | MATERIA | L: HIG | H CONDUCT | TIVITY WROUGHT CO | PPER | | G | | | | | | | | | |
| С | FINISH: | ELE | CTOR-TIN F | LATE UNLESS OTHE | RWISE | | | | " | | | | | | | С |
| J | | | | ΓE PER MIL - T -16366 D.WITH "SP" FOR SILV | | | | | | | | | | | | |
| | | 00. | | 5 | | | , | ** | Color cod | led barı | rel ma | rkings | | | | |
| | | | | | | | 2 | | \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\ | | ما ما | | | | | |
| _ | INSTALLATION GUIDE | | | | | | Wire inspection hole B D | | | | | | | | 1 | |
| | DIE CODE | = 24 | | | | | 7 | | `\rangle | | - | | | ¦ | | |
| | DIE COLO | R = Blue | | | | | <u> </u> | | | | | 7 | | | | |
| | | | | | | | | Beve | eled wire entry | | | | | ! | | |
| | | | | , | | | | | • | | | | | | | |
| В | | را) د |) | V | | | | | | | | | | | | В |
| | | | | ROHS 2002/95/EC | | | | | | | | | | | | |
| | | LIS' | TED | | | | | | | | | | | | | |
| | | ZMVV/2/7/ | | | | | | | | | | | | | | |
| _ | | | | | | | | | | | | | | | | _ |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | HUY | | ELES | | | | | _ | |
| | | | | | | | | | | 76. Hua | | | | | | |
| ٨ | | | | | | | | www.huyac | | Panyu [| | | | | | _ |
| Α | | | | | | | TIT | TLE WIRE | CONNECT | ORS | AND |) SO | LDEF | RING | | Α |
| | | | | | | | | LUGS | FOR CODE | E ANI |) FL | EX C | CABL | Е | | |
| | 00 23-Aug- | 25 Ruby Feng | Sinia Qiu | Celestra S | tandards Spec. Initia | ıled. | | ATERIAL HIGH-CONDU WROUGHT C | OPPER DB061 | 034F-25 | 1 | | TS | RID ANGLE PE | ROJECTION | |
| ı | REV DAT | DWN | CHK | DE | SCRIPTION | | ECN FIN | ELECTRO TIN | PLATE DWG. NO. | 186-cp34 | ·51 | init 1N | ICH - | (E) | \Box | ı |
| | | 4 | | | 3 | | \triangle | 2 | | | | | 1 | | | |
| | - | | | • | | | I | | | | • | | | | | |