			4		I		3	\downarrow	7		2		1		1			
I	DISCL	OSED IN CON	VFIDENCE AND	NOT TO BE	PROERTY OF CELE REPRODUCED, USE			Ī	CELESTRA CAT.NO	A WI CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D ±0.015	G ±0.02	H ±0.01]
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				ŀ	DB061021F-2		#6 Weld 61/2 24.6 kcmil		2.04	0.46	0.08	1.50	0.27	1
								L		I	21.0 1011		1		1			1
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													D				
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																	
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER								G G									
С	F	INISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
	Color coded barrel markings																	
\rightarrow	INSTALLATION GUIDE DIE CODE = 24 DIE COLOR = Blue								Beveled wire entry									
В			. (1))	\mathbf{V}							,						В
	LISTED WIRE CONNECTORS 2MVV/2/7/8.E513813													_				
A												CELES	STRA		RPOI	RATIO	ON	1
								HUY www.huyac		76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.								
										TITLE WIRE CONNECTORS AND						SOLDERING		
											FOR CO	de an						
			Ruby Feng		Celes		ds Spec. Initialed.			MATERIAL HIGH-CONDU WROUGHT C	DETIVITY PRT. NO COPPER DE DWG. NO	061021F-25	1	INIT	TS -			
	REV	DATE	DWN 4	СНК		DESCRIF	3	1		ELECTRO TIN		186-cp34	452 ⁰ 	IN	існ 1	ΨĽ]
			-		I		0	4		2			I		1			