	_						I									$\overline{}$
		4			3		7	2					1			
ı				PROERTY OF CELESTRA, REPRODUCED, USED OR	IS		CELESTRA		RE SIZE	BOLT	В	С	D	G	Н	
		EPT FOR WHICH		REPRODUCED, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
							DB061458F-26	1 #6 AWG	#6 Weld 61/24 = 24.6 kcmil	?1/4	1.26	0.48	0.08	0.62	0.27	
								-						•		
D																D
	NOTE:		DIMENSION ECIFIED.	IS ARE IN INCHES UN	LESS OTHERWISE											
				B,WP AND J SERIES (DERWRITERS INC." AI			DOLT SIZE									
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.							BOLT SIZE								
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															
	MATERIA	L: HIG	H CONDUCT	TIVITY WROUGHT CO	PPER		G									
С	FINISH:	ELE	CTOR-TIN P	LATE UNLESS OTHER	RWISE											С
C				TE PER MIL - T -16366. D.WITH "SP" FOR SILVI												
		001	TIX OAT.NO		LIK.		λ	*/	Color cod	ed barı	rel ma	rkings				
							. /		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \							
_	INSTALLATION GUIDE						Wire inspection hole								1	
	DIE CODE	= 24					4		B		-	L D		¦	l	
	DIE COLC	R = Blue					<u> </u>					+				
								Beve	eled wire entry	·						
				,					,							
В		, (u														В
				ROHS 2002/95/EC												
		LIS	TED													
		WIRE CON ZMVV/2/7/														
_																_
								HUY		ELES						
										76. Hua					n.	
٨								www.huyac		Panyu [٨
Α							TIT	wire.	CONNECT	ORS	AND) SOI	LDEF	RING		Α
								LUGS	FOR CODE	AN[) FL	EX C	CABL	Е		
	00 23-Aug-	25 Ruby Feng	Sinia Qiu	Celestra St	andards Spec. Initiale	d	MA	TERIAL HIGH-CONDU WROUGHT C	JCTIVITY PRT. NO. COPPER DB061	458F-261	1 S	CALE N	TS THE	RID ANGLE PF	ROJECTION	
ı	REV DATE	DWN	CHK	DES	SCRIPTION		ECN FIN	ISH ELECTRO TIN	I PLATE DWG. NO.	86-cp34	63 ^U	INIT IN	ICH -	(E	\exists	ı
		4			3		Λ	2	•		i		1			
	-			•							•					