	-						1										
		4			3		4	7	2					1			
ı				PROERTY OF CELEST				CELESTRA	WI	RE SIZE	BOLT	В	С	D	G	Н	
	DISCOSED IN C			REPRODUCED, USED	OR		-	CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
								WP061401F- 113	- #6 AWG	#6 Weld 61/24 = 24.6 kcmil	?1/4	1.15	0.44	0.09	1.00	0.26	
							L					l		-			
D																	D
_	NOTE:		DIMENSION CIFIED.	IS ARE IN INCHES	UNLESS O	THERWISE											
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. BOLT SIZE																
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	MATERIAL	: HIGH	H CONDUCT	IVITY WROUGHT	COPPER					G							
С	FINISH:	ELEC	CTOR-TIN P	LATE UNLESS OTH	HERWISE												С
C				E PER MIL - T -163 .WITH "SP" FOR SI													
		3011	FIX CAT.NO	.WITH SF FOR SI	LVLN.				*	_Color cod	led barı	rel ma	rkings				
					Wire inspection hole												
	INSTALLATEDIE CODE	TION GUIDE						4		∫ B_		-⊶	D				\leftarrow
	DIE COLOI							<u> </u>					†				
									_				Ŷ				
									⁻Beve	eled wire entry							
В				./													В
Ь		c(V	L)us	.RoHS.													Ь
		1107		2002/95/EC													
		LIS I															
		ZMVV/2/7/8.	.co13913														
_	-																_
		1 1						1 1		. 1							
									HUY		ELES					_	
											76. Hua					n.	
٨									www.huyac		Panyu [_
Α								TI	TLE WIRE	CONNECT	ORS	AND) SO	LDEF	RING		А
									LUGS	FOR CODI	E ANI) FL	EX C	CABL	Ε		
	00 23-Aug-2	5 Ruby Feng	Sinia Qiu	Celestra	Standards	Spec. Initialed.		M.	ATERIAL HIGH-CONDU WROUGHT O	JCTIVITY PRT. NO.	401F-11	3 S	CALE N	TS THE	RID ANGLE PF	ROJECTION	
	REV DATE	_	СНК		DESCRIPT	·		ECN FII	NISH ELECTRO TIN	DWG NO	186-cp34		INIIT	ICH .	\P E	\exists	_
		4		I		3	Δ	\	2		-1		- 11	1	•		
		-		I	`	-	4		_			I					