_	,					1										
		4   3		3	$\forall$		2					1				
ı		ON ON THIS DRAWING I					CELESTRA		RE SIZE	BOLT	В	С	D	G	Н	
		ONFIDENCE AND NOT <sup>-</sup> PT FOR WHICH FURNIS		D, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	l
					_	l w	/P061401F- 113	#6 AWG	#6 Weld 61/24 = 24.6 kcmil	?1/4	1.15	0.44	0.09	1.00	0.26	
							,									ĺ
D																D
	NOTE:	1. ALL DIMEN SPECIFIED	NSIONS ARE IN I	NCHES UNLESS	OTHERWISE											
		2 ALL DA DE	3,LA,LB,WP AND	LSERIES OF CA	AT NO S ARE											
		LISTED BY	"UNDERWRITE	RS INC." AND "C	SA" FOR USE							BOLT	SIZF			l
		ON CODE	WIRES AND FLE	X/24 STRANDEI	D CABLES.				Λ   <b>~</b>		$\mathbf{x}$	Ţ	0			l —
			AT.NO.WITH "L"						Heya H	-(-X)-	- c					l
		WITH "P".	SE SPECIFIED IN	THE SUFFIX O	F THE CAT.NO.				\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	X		<u> </u>				l
	MATERIAL	: HIGH CON	DUCTIVITY WRO	UGHT COPPER	<b>!</b>				G							
С	FINISH:	ELECTOR-	TIN PLATE UNLE	SS OTHERWIS	E											С
O			PLATE PER MIL T.NO.WITH "SP"													
		001111101		TOTA GILVETA			λ	*	Color cod	ed barr	el mai	rkings				l
									/ ,,,,,							l
_	INSTALLATION GUIDE						Wire inspection hole  B D									_
	DIE CODE						4		B	1	-	D				
	DIE COLOI	R = Blue					<u> </u>					‡				l
								Reve	led wire entry	ı		1				
								Deve	iled wife entry				Li			
В			•													В
	۱ ,	· (II) <sub>II</sub> , <sub>P</sub>														l
	·		02/95/EC													
		WIRE CONNECTORS ZMVV/2/7/8.E513913														
	1															
										ELES	TPA	COI	SDUE	ΣΔΤΙΛ	ואכ	
							_	HUY	A	'6. Hua						l
		+ +-						ww.huyac		Panyu D						
Α				TITL	- \//IDF	CONNECT	)RS			DED	INC		Α			
			UGS FOR CODE AND FLEX CA													
										AINL						
	00 27-Oct-2	5 Ruby Feng Sinia		Celestra Standa	rds Spec. Initialed.			ERIAL HIGH-CONDU WROUGHT C	OPPER WP061	401F-113	3	CALE N7	rs	ID ANGLE PF	OJECTION	
1	REV DATE	DWN C	HK	DESCRI	PTION		ECN FINIS	ELECTRO TIN	PLATE DWG. NO. 1	86-cp346	69 U	nit <b>IN</b>	сн 📗	<b>⊕</b> €		
		4			3	Φ		2					1			
			•								•					