									1									
			4				3	7	\bigvee		2				1			
1				AWING IS THE I D NOT TO BE F					CELESTRA	·	IRE SIZE	BOLT	В	С	D	G	Н	'
			FOR WHICH		KEI KODOCED	, OSED ON			CAT.NO	CODE	#6 Weld 61/24 =	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	ł
									LB061458F-2	260 #6 AWG	24.6 kcmil	?1/4	1.26	0.45	0.08	0.62	0.26	
D																		D
	NO	OTE:		DIMENSION CIFIED.	S ARE IN IN	CHES UNLES	SS OTHERWISE											
			2 All	DADBIALE	R WP AL AS	AND J SERIE	S OF CAT.NO.S	ARF										
			LIST	ED BY "UND	ERWRITER	S INC." AND "	CSA" FOR USE	<u> </u>	∠BOLT SIZE									
			ON	CODE WIRE	S AND FLEX	/24 STRANDE	ED CABLES.				Q		\mathbf{A}^{\prime}	T				 —
							P HOLE UNLESS OF THE CAT.NO.			(Huya	-(- X	- - c	;				
				H "P".	LOII ILD IIV	THE GOLLIA	OF THE OAT.NO.	•			1			V				
	M	ATERIAL:	HIG	HIGH CONDUCTIVITY WROUGHT COPPER G														
С	FII	NISH:			_	SS OTHERWI	SE											c
				CIFED PLAT		T -16366. FOR SILVER.												
										\ <u>\</u>	Color cod	led barı	el ma	rkings				
									_ ش		//////////////////////////////////////	spectio	n hole	7				
\triangle	IN	ISTALLATIC	ON GUIDE						45.	piego,	В	iopeotio	11 11010	, D		\vdash		4
		IE CODE = 2 IE COLOR =									`\		•	Ī				
		ic coloit -	- Dide						<u> </u>					+				
			Beveled wire entry															
_																—		_
В		/	(ii)	~														В
		c (RoHS 2002/95/EC														
			ISTED E CONNECTORS IV/2/7/8.E513913															
		ZM	/V/2/7/8.E513913															
												ELES	TD	<u> </u>	RDO!	ΡΔΤΙ	ON.	
										HU		76. Hua						
										www.huyac		Panyu [
Α								TITLE WIRE CONNECTORS AND SOLDER						RING		Α		
									LUGS FOR CODE AND FLEX CABLE									
	00	15-Dec 25	Ruby Feng	Sinia Oiu		`alastra Stand	ards Spec. Initiale		N.	MATERIAL HIGH-COND	UCTIVITY PRT. NO.		S	CALE	ТНЕ	RID ANGLE PI	ROJECTION	1
	REV	DATE	DWN	CHK			RIPTION	Ju.	ECN F	WROUGHT (81118 118	458F-260 186-cp34		INIT	TS .	(1)	\Box	
	1 V L V	DATE	4	J. 111	1	- DE001	3		1 -014	ELECTRO TIN	N PLATE	100 - 6µ34		IN	1CH	Y	7	¹
			7		I		J	2		2			l		'			