	-																
	4			3		\checkmark	☆ 2						1		_		
I				PROERTY OF CELE REPRODUCED, USE				CELESTRA		IRE SIZE	BOLT	В	С	D	G	Н	
		EXCEPT FOR WH					+	CAT.NO	CODE	FLEX 40-50 Navy 91/2	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
								DB041458F-2	50 #4 AWG	= 36.7 kcmil	1/4	1.25	0.55	0.09	0.63	0.33	
							L			133/.0177 49/.02	9						
D																	D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	MATE	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER															
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.														С		
	Color coded barrel markings										rkings						
\rightarrow		INSTALLATION GUIDE							Wire inspection hole								
Ľ		DDE = 29 DLOR = Gray						A		B		-	D)		7
													+	\rightarrow	<u> </u>		
									Bow	eled wire entry	I		I				
Б			\frown	./					Dev	eled wire entry							
В		c	VL)us	RoHS													В
				2002/95/EC													
			E CONNECTORS														
		ZM	V/2/7/8.E513913														
	-																—
				1						. 1							-
									HU	R	CELES						
А									www.huyad		76. Hua Panyu I						
A								WIRE CONNECTORS AND SOLDERING								A	
						LUGS FOR CODE AND FLEX CABLE											
	00 23-A	ug-25 Ruby F	eng Sinia Qiu	Celes	stra Standa	rds Spec. Initialed.		N	IATERIAL HIGH-COND WROUGHT	UCTIVITY PRT. NO. COPPER DB04	1458F-25		CALE N		RID ANGLE PF	ROJECTION	1
	REV D	ATE DW	N СНК		DESCRI	PTION		ECN F	INISH ELECTRO TII	DWG NO	186-cp35	_	NIT	СН	ŒE		
	•	4				3	Δ		2	1		İ		1			-
L	-			'								I					