								1										
			4				3	7	7		2				1			
ı					PROERTY OF C				CELESTR	A W	RE SIZE	BOLT	В	С	D	G	Н	'
			FOR WHICH		REPRODUCED,	USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04 ±	±0.015	±0.02	±0.01	
							_		LB041458	F #4 AWG	40-50 Navy 91/24 = 36.7 kcmil 133/.0177 49/.029	1/4	1.19	0.52	0.10	0.62	0.32	
D																		D
D	NC	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													D			
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. BOLT SIZE																	
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	MA	ATERIAL:	HIG	H CONDUCT	TIVITY WROU	GHT COPPER	1											
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С					
										, *\	Color cod	led barre	el mark	kings				
	INSTALLATION GUIDE DIE CODE = 29 DIE COLOR = Gray								Wire inspection hole B D									
В	CUL US ROHS													В				
		MIR ZM	IE CONNECTORS V/27/16 EB13813															_
										HU\ www.huyac		ELES 76. Huar Panyu D	ncun R	Rd. Zho	ngcu	n Towr		
Α									-	TITLE WIRE CONNECTORS AND SOLDERING '							Α	
										LUGS FOR CODE AND FLEX CABLE								
	00	27-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				d.		WROUGHT COPPER LB041458F NTS						D ANGLE PR	DJECTION			
1	REV	DATE	DWN	CHK		DESCRI	PTION		ECN	ELECTRO TIN	PLATE DWG. NO.	186-cp354	6 UNI	IT INCI	Н ($\bigoplus \Box$	\exists	1
			4				3	4		2					1			
								ı										