			1		1		3	+		,	2				1			
					PROERTY OF C REPRODUCED,			CELE CAT			RE SIZE FLEX	BOLT SIZE	B MIN ±	C D		H ±0.01		
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				DB023		#2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil			0.60 0.1		0.36		
D	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.												D				
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. BOLT SIZE																	
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
С		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С				
\rightarrow	INSTALLATION GUIDE DIE CODE = 33										Color coded barrel markings Wire inspection hole B D							
		DIE COLOR :						į		Beve	eled wire entry		1	?				
В				US	RoHS 2002/96/EC	l											В	
			WIRE CON- ZMVV/2/7/8														_	
										IUY ww.huyac	A	76. Huan	cun R	CORP(d. Zhong angzhou	cun Tow	'n.		
Α									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								А	
		23-Aug-25	-		Ce		ds Spec. Initialed.			WROUGHT C	OPPER DB02	23801F	SCA	NTS	THRID ANGLE P	ROJECTION		
	REV	DATE	4	CHK	I	DESCRI	TION 3	ECN	1 LIMISH	ELECTRO TIN	PLATE DWG. NO.	86-cp3578	3 UNII	INCH	1		I	
			- ∓		I			4		_			I		1			