	-		1		1		3	+		2	1		1			
					PROERTY OF CEL REPRODUCED, US			CELESTI CAT.NO	RA W	IRE SIZE	BOLT E	B C	D ±0.015	-	H .01	
	DISLO	SED EXCEPI	FOR WHICH	FURNISHED.	·			DB025634F	3322	FLEX 60 Navy #4 Weld 125/24 = 50.5 kcmil	5/16 1.				37	
D	N	IOTE:		DIMENSION CIFIED.	IS ARE IN INCH	ES UNLESS	OTHERWISE							 	D	
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. BOLT SIZE															
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER G															
С	F													С		
									*\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Color cod	ed barrel ı	markings				
	D	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown							Wire inspection hole B D							
В		Beveled wire entry RoHS 2002/95/EC													В	
		WIRE CONNECTORS ZMVV/2/7/8.E513813														
									HU\ www.huyad		ELESTI '6. Huanc Panyu Dist	un Rd. Zł	nongcur	n Town.	ı	
А									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							
	00	23-Aug-25	Ruby Feng	by Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE NTS				TS /	ANGLE PROJEC	TION	
ı	REV	DATE	DWN	CHK		DESCRIF		ECN	FINISH ELECTRO TII	N PLATE DWG. NO. 1	86-cp3582	UNIT	1CH /		<u> </u>	
	-		4				3	4	2				1			