	_																
		4				3	_	7	2	2				1			
l				PROERTY OF CELES			`	CELESTRA	WI	RE SIZE	BOLT	В	С	D	G	Н	1 '
	DISCLOSED IN O			REPRODUCED, USE	D OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04		±0.02	±0.01	1
						I		DB021434F-26	61 #2 AWG	150/24 #2 Weld	?1/4	1.39	0.68	0.10	0.75	0.41	1
_																	
D	NOTE:	4 11	DIMENSION	JO ADE IN INCHE	C LINII ECC	OTHEDWISE											D
	NOTE.	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.															
		2 All	DA DRIAI	B WP AND J SER	UES OF CA	T NO S ARE	S ARE										
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 						BOLT SIZE									
_	1	ON	CODE WIRE	S AND FLEX/24 S													
		PRE	FIX CAT.N	O.WITH "L" HAS N	NOT PEEP H	HOLE UNLESS		- C									
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
								_ G									
	MATERIAL	.: HIG	H CONDUC	TIVITY WROUGH	T COPPER												
С	FINISH:		ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.												С		
				D.WITH "SP" FOR				∠ Color coded barrel markings									
								, č., /	E old	Wire ir	spectio	n hole)				
							Wire inspection hole B D										
	INSTALLA DIE CODE	TION GUIDE = 33								£		1			1		\leftarrow
	DIE COLO							1	\				4				
									[∖] Beve	led wire entry					!		
_				./													
В		_ (Ŭ	L) _{IIS}	PoHS													В
		0		2002/95/EC													
		LIS'	TED														
		ZMVV/2/7/															
_																	
											ELES	STRA	CO	RPOI	RATIO	ON	
						-			HUY		76. Hua						
			-						www.huyac		Panyu [
Α								TITLE WIRE CONNECTORS AND SOLDERING								Α	
		LUGS FOR CODE AND FLEX CAB															
								-ARL	<u> </u>								
	00 23-Aug-2	25 Ruby Feng	Sinia Qiu	Celes	tra Standard	ds Spec. Initialed.		MA	ATERIAL HIGH-CONDL WROUGHT C	OPPER PRT. NO. DB021	434F-26	1 S	CALE N	TS THE	RID ANGLE PI	ROJECTION	
	REV DATE		CHK		DESCRIP	PTION		ECN FIN	NISH ELECTRO TIN	DWG NO	186-cp35		INIIT	ICH .	(E		
		4	I	1		3			2			1		1	'		'
	-	7		I		5	_		۷			I					